

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Arc welding equipment –
Part 10: Electromagnetic compatibility (EMC) requirements**

**Matériel de soudage à l'arc –
Partie 10: Exigences de compatibilité électromagnétique (CEM)**

IEC 60974-10:2007

<https://standards.iteh.ai/catalog/standards/iec/60974-10:2007>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Arc welding equipment –
Part 10: Electromagnetic compatibility (EMC) requirements**

**Matériel de soudage à l'arc –
Partie 10: Exigences de compatibilité électromagnétique (CEM)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

T

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	7
4 General test requirements	8
4.1 Test conditions	8
4.2 Measuring instruments	8
4.3 Artificial mains network	8
4.4 Voltage probe.....	8
4.5 Antennas.....	8
5 Test set-up for emission and immunity.....	8
5.1 General.....	8
5.2 Load.....	10
5.3 Ancillary equipment.....	10
5.3.1 General requirements	10
5.3.2 Wire feeders.....	10
5.3.3 Remote controls	11
6 Emission tests	11
6.1 Classification for r.f. emission tests	11
6.1.1 Class A equipment	11
6.1.2 Class B equipment	11
6.2 Test conditions.....	11
6.2.1 Welding power source	11
6.2.2 Load	12
6.2.3 Wire feeders.....	12
6.2.4 Ancillary equipment	12
6.3 Emission limits.....	13
6.3.1 General	13
6.3.2 Mains terminal disturbance voltage.....	13
6.3.3 Electromagnetic radiation disturbance	14
6.3.4 Harmonics, voltage fluctuations and flicker	14
7 Immunity tests	14
7.1 Classification.....	14
7.1.1 Applicability of tests.....	14
7.1.2 Category 1.....	14
7.1.3 Category 2.....	15
7.2 Test conditions.....	15
7.3 Immunity performance criteria	15
7.3.1 Performance criterion A.....	15
7.3.2 Performance criterion B.....	15
7.3.3 Performance criterion C.....	15
7.4 Immunity levels	15
8 Documentation for the purchaser/user	17
Annex A (informative) Installation and use	18

Annex B (informative) Limits	20
Figure 1 – Typical arc welding equipment with a conventional load	9
Figure 2 – Position of arc welding equipment and conventional load with respect to the antenna	9
Table 1 – Immunity levels – Enclosure	16
Table 2 – Immunity levels – AC input power port.....	16
Table 3 – Immunity levels – Ports for process measurement and control lines	16
Table B.1 – Mains terminal disturbance voltage limits, idle state	20
Table B.2 – Mains terminal disturbance voltage limits, load conditions	20
Table B.3 – Electromagnetic radiation disturbance limits, idle state	21
Table B.4 – Electromagnetic radiation disturbance limits, load conditions	21
Table B.5 – Maximum permissible harmonic current for non-professional equipment with input current $I_{1\max} \leq 16$ A	21
Table B.6 – Current emission limits for professional equipment with $I_{1\max} \leq 75$ A other than balanced three-phase equipment	22
Table B.7 – Current emission limits for professional balanced three-phase equipment with $I_{1\max} \leq 75$ A.....	22
Table B.8 – Current emission limits for professional balanced three-phase equipment with $I_{1\max} \leq 75$ A under specified conditions	22
Table B.9 – Limits for arc welding equipment with $I_{1\max} \leq 75$ A.....	23

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ARC WELDING EQUIPMENT –

Part 10: Electromagnetic compatibility (EMC) requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60974-10 has been prepared by IEC technical committee 26: Electric welding.

This second edition cancels and replaces the first edition published in 2002 and amendment 1 (2004) and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- application of more stringent r.f. emission limits for the idle state;
- mandatory classification of arc starting and stabilizing devices as Class A equipment;
- additional immunity tests (surges and r.f. common-mode currents);
- inclusion of informative Annex B, containing the applicable emission limits for information of the user of the standard.

The text of this standard is based on the following documents:

CDV	Report on voting
26/341/CDV	26/356/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60974 series, under the general title *Arc welding equipment*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The contents of the corrigendum of June 2011 have been included in this copy.

ARC WELDING EQUIPMENT –

Part 10: Electromagnetic compatibility (EMC) requirements

1 Scope

This part of IEC 60974 specifies

- a) applicable standards and test methods for radio-frequency (r.f.) emissions;
- b) applicable standards and test methods for harmonic current emission, voltage fluctuations and flicker;
- c) immunity requirements and test methods for continuous and transient, conducted and radiated disturbances including electrostatic discharges.

This standard is applicable to equipment for arc welding and allied processes, including power sources and ancillary equipment, for example wire feeders, liquid cooling systems and arc striking and stabilizing devices.

NOTE 1 Allied processes are, for example, plasma cutting and arc stud welding.

NOTE 2 This standard does not specify basic safety requirements for arc welding equipment such as protection against electric shock, unsafe operation, insulation coordination and related dielectric tests.

Arc welding equipment type tested in accordance with, and which has met the requirements of, this standard is considered to be in compliance for all applications.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-161, *International Electrotechnical Vocabulary – Chapter 161: Electromagnetic compatibility*

IEC 60050-851, *International Electrotechnical Vocabulary – Chapter 851: Electric welding*

IEC 60974-1, *Arc welding equipment – Part 1: Welding power sources*

IEC 60974-3, *Arc welding equipment – Part 3: Arc striking and stabilizing devices*

IEC 60974-6, *Arc welding equipment – Part 6: Power sources for manual metal arc welding with limited duty*

IEC 61000-3-2:2005, *Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)*

IEC 61000-3-3:1994, *Electromagnetic compatibility (EMC) – Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems for equipment with rated current ≤ 16 A per phase and not subject to conditional connection¹*

Amendment 1 (2001)

Amendment 2 (2005)

¹ There exists a consolidated edition 1.2 (2005) that includes edition 1 and its amendments 1 and 2.

IEC/TS 61000-3-4, *Electromagnetic compatibility (EMC) – Part 3-4: Limits – Limitation of emission of harmonic currents in low-voltage power supply systems for equipment with rated current greater than 16 A*

IEC 61000-3-11:2000, *Electromagnetic compatibility (EMC) – Part 3-11: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems – Equipment with rated current ≤ 75 A and subject to conditional connection*

IEC 61000-3-12:2004, *Electromagnetic compatibility (EMC) – Part 3-12: Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current > 16 A and ≤ 75 A per phase*

IEC 61000-4-2, *Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test*

IEC 61000-4-3, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*

IEC 61000-4-4, *Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test*

IEC 61000-4-5, *Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test*

IEC 61000-4-6, *Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields*

IEC 61000-4-11, *Electromagnetic compatibility (EMC) – Part 4-11: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity tests*

CISPR 11:2003, *Industrial, scientific and medical (ISM) radio-frequency equipment – Radio disturbance characteristics – Limits and methods of measurement*

CISPR 14-1, *Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission*

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-2, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Ancillary equipment – Conducted disturbances*

CISPR 16-1-4, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Ancillary equipment – Radiated disturbances*

3 Terms and definitions

For the purposes of this document, the terms and definitions related to EMC and to the relevant phenomena contained in IEC 60050-161, the terms and definitions related to arc welding equipment contained in IEC 60050-851 and in IEC 60974-1, as well as the following, apply.

3.1 click

disturbance which exceeds the limit of continuous disturbance no longer than 200 ms and which is separated from a subsequent disturbance by at least 200 ms

NOTE 1 Both intervals are related to the level of the limit of continuous disturbance.

NOTE 2 A click may contain a number of impulses, in which case the relevant time is that from the beginning of the first to the end of the last impulse.

3.2

idle state

operating state in which the power is switched on and the welding circuit is not energized

NOTE For some types of equipment, there is no idle state, but a welding state preceding arc striking.

4 General test requirements

4.1 Test conditions

Tests shall be carried out within the specified operating conditions for the apparatus, as given in IEC 60974-1 or IEC 60974-6, and at its rated supply voltage and frequency. Results obtained for r.f. emission and immunity at 50 Hz are valid for the same model operating at 60 Hz and vice versa.

4.2 Measuring instruments

The measuring equipment shall comply with the requirements of CISPR 16-1-1 and the standards referred to in Tables 1, 2 and 3 as applicable.

4.3 Artificial mains network

Measurement of the mains terminal disturbance voltage shall be made using an artificial mains network consisting of 50 Ω /50 μ H V-network as specified in CISPR 16-1-2.

The artificial network is required to provide a defined impedance at r.f. across the mains supply at the point of measurement and also to provide for isolation of the equipment under test from ambient noise on the power lines.

4.4 Voltage probe

A voltage probe shall be used when the artificial mains network cannot be used. The probe is connected sequentially between each line and the reference earth. The probe shall consist of a blocking capacitor and a resistor such that the total resistance between the line and earth is at least 1 500 Ω . The effect on the accuracy of measurement of the capacitor or any other device which may be used to protect the measuring receiver against dangerous currents shall be either less than 1 dB or allowed for in calibration.

4.5 Antennas

In the frequency range from 30 MHz to 1 GHz, the antenna(s) used shall be as specified in CISPR 16-1-4. Measurements shall be made for both horizontal and vertical polarization. The nearest point of the antenna(s) to the ground shall be not less than 0,2 m.


5 Test set-up for emission and immunity

5.1 General

Emission and immunity testing shall be carried out on equipment configured in accordance with Figure 1. Arc welding equipment tested in such a configuration shall be considered to have met the necessary requirements of this standard.

If due to the design of the arc welding equipment, these tests cannot be carried out as described, the manufacturer's recommendations (for example, temporary bypassing or disablement of control circuits) should be followed in order to match these test objectives. Any temporary changes to the arc welding equipment shall be documented.

The configuration of the equipment under test shall be noted in the test report.




Key

- | | | | |
|---|---------------------------------|----|--------------------------------|
| 1 | Wire feeder | 7 | Insulation |
| 2 | Welding power source | 8 | Earthed ground plane |
| 3 | Welding cable (bundled) | 9 | Liquid cooling systems |
| 4 | Interconnection cable (bundled) | 10 | Input supply cable |
| 5 | Remote control | 11 | Remote control cable (bundled) |
| 6 | Conventional load | | |
| a | = 1 m | b | ≤ 0,4 m |

NOTE Items 1, 5, 9 and 11 are ancillary equipment, as applicable.

Figure 1 – Typical arc welding equipment with a conventional load



Key

- | | | | |
|---|-----------------------|---|-----------------------------|
| W | Arc welding equipment | A | Antenna |
| 3 | Welding cable | 6 | Conventional load |
| a | = 1 m | c | See IEC 61000-4-3 and 6.3.3 |

Figure 2 – Position of arc welding equipment and conventional load with respect to the antenna

If ancillary equipment can be connected to the welding power source, then the welding power source shall be tested with the minimum configuration of ancillary equipment necessary to exercise the ports. If the welding power source has a large number of similar ports or ports with many similar connections, then a sufficient number shall be selected to simulate actual operating conditions and to ensure that all the different types of termination are covered.

For conducted r.f. emission tests the welding power source shall be connected to the electricity supply using the V-network specified in 4.3 whenever possible. The V-network shall be located so that its closest surface is no less than 0,8 m from the nearest boundary of the equipment under test. The input cable shall have a minimum length of 2 m.

The welding power source shall be connected to the conventional load by welding cables of suitable cross-section for the welding current, or the appropriate torch or electrode holder with adapter. The welding cables shall have a minimum length of 2 m.

For r.f. emission tests the welding power source shall be insulated by an insulating mat (or blocks) not greater than 12 mm thick or insulated by its own under-gear if appropriate.

For radiated emission and immunity tests, the welding power source and conventional load shall be positioned equidistant from the test antenna; see Figure 2.

The cables shall be allowed to fall naturally to the ground plane. Excess input, welding or torch cables shall be folded to and forth, as far as practicable, to form a bundle not exceeding 0,4 m in length.

Specific test set-up geometries for immunity tests can be found in the basic standards referenced in Tables 1, 2 and 3.

5.2 Load

During the tests, the arc welding operation is simulated by loading the equipment with a conventional load as specified in IEC 60974-1. For r.f. emission tests the conventional load shall be insulated by an insulating mat (or blocks) not greater than 12 mm thick or insulated by its own under-gear if appropriate.

5.3 Ancillary equipment

5.3.1 General requirements

Ancillary equipment shall be tested in conjunction with a welding power source. It shall be connected and installed as recommended by the manufacturer.

Specific requirements for wire feeders and remote controls are given below.

5.3.2 Wire feeders

Wire feeders shall be positioned on/by a welding power source as designed. Wire feeders, which can be located both inside or outside the welding power source enclosure, shall be placed outside. For r.f. emission tests, wire feeders designed to be placed on the floor shall be insulated from it, by an insulating mat (or blocks) not greater than 12 mm thick or insulated by its own under-gear, if appropriate.

The welding cable connecting the wire feeder to the welding power source shall be 2 m in length or longer, if required, to make the connection and be of suitable current rating. If a welding cable in excess of 2 m is provided by the manufacturer, the excess shall be folded to and forth, as far as practicable, to form a bundle not exceeding 0,4 m in length. A welding cable connection less than 2 m long shall be permitted if this is supplied with the equipment.

The interconnection cable(s) between the wire feeder and the welding power source shall be of the type and length recommended by the manufacturer. Excess cable shall be folded to and forth, as far as practicable, to form a bundle not exceeding 0,4 m in length.

A welding torch, as recommended by the manufacturer, may be used instead of a welding cable to make the connection from the wire feeder to the conventional load.

5.3.3 Remote controls

If a welding power source is capable of operating with a remote control, it shall be tested with the remote control connected, which is expected to give the highest emissions and/or lowest immunity. The remote control shall be placed on, and insulated from, the ground plane beside the load, where possible. For r.f. emission tests, the insulation shall not be greater than 12 mm thick. Remote controls designed to be attached to the arc welding equipment during use shall be placed as intended.

Excess cable shall be folded to and forth to form a bundle not exceeding 0,4 m in length, as far as practicable.

6 Emission tests

6.1 Classification for r.f. emission tests

6.1.1 Class A equipment

Class A equipment is intended for use in locations other than residential locations where the electrical power is provided by the public low-voltage supply system.

Class A equipment shall meet Class A limits in accordance with 6.3.

6.1.2 Class B equipment

Class B equipment is suitable for use in all locations, including residential locations where the electrical power is provided by the public low-voltage supply system.

Class B equipment shall meet Class B limits in accordance with 6.3.

6.2 Test conditions

6.2.1 Welding power source

6.2.1.1 Test conditions for r.f. emission tests

The welding power source shall be tested at the conventional load voltages referenced in 6.2.2 under the following output conditions:

- a) at rated minimum welding current;
- b) at rated welding current at 100 % duty cycle.

Additionally, if there is an idle state, the welding power source shall be tested in this condition with the configuration shown in Figure 1, with the load disconnected.

If the primary current is greater than 25 A at any of the output conditions given above, the output may be reduced to give a primary current of 25 A. However, if a primary current of 25 A or less cannot be achieved, the voltage probe, as specified in 4.4, may be used in 6.3.2 as an alternative to an artificial mains network.

Welding power sources capable of operating in both a.c. and d.c. modes shall be tested in both modes.

Multi-process welding power sources shall be tested with the conventional load which gives the highest load voltage for the set current. If a welding power source contains more than one output circuit (for example, plasma cutting and manual arc welding), each circuit shall be tested separately.

For power sources with an external wire feeder, only the MIG configuration shall be tested with the MIG conventional load voltage.

6.2.1.2 Test conditions for harmonics

Welding power sources within the scope of IEC 60974-1 shall be tested at the conventional load voltage according to the process as given in 6.2.2 at maximum rated welding current at the rated duty cycle. The observation period shall be 10 min.

Welding power sources capable of operating in both a.c. and d.c. modes shall be tested in both modes.

Multi-process welding power sources shall be tested with the conventional load which gives the highest conventional load voltage for the set current.

Test conditions for welding power sources within the scope of IEC 60974-6 are given in IEC 61000-3-2.

6.2.1.3 Test conditions for voltage fluctuations and flicker

Test conditions for welding power sources are given in IEC 61000-3-3.

6.2.2 Load

Conventional load voltages are given in IEC 60974-1 or IEC 60974-6.

6.2.3 Wire feeders

Wire feeders shall be tested at 50 % of the maximum wire feed speed setting, where possible. Pre-programmed and synergic wire feeders shall be tested according to the output setting of the welding power source.

During this test, pressure shall be removed from the drive rolls of the wire feeder and the welding power source shall be loaded as given in 6.2.1.1.

6.2.4 Ancillary equipment

Other ancillary equipment shall be tested according to the manufacturer's recommendations.

Arc striking and stabilizing devices and arc stud welding equipment shall be classified as Class A equipment. For arc striking and stabilizing devices which are energy limited in accordance with IEC 60974-3, no additional r.f. emission tests are required.