
Prostori za gledalce – 4. del: Lastnosti sedežev

Spectator facilities - Part 4: Seats - Product characteristics

Zuschaueranlagen - Teil 4: Sitze - Produktmerkmale

Installations pour spectateurs - Partie 4: Sieges - Caractéristiques des produits

Ta slovenski standard je istoveten z: EN 13200-4:2006*SIST EN 13200-4:2007**<https://standards.iteh.ai/catalog/standards/sist/4553067f-fa9f-4a1d-a297-ab560aa40d53/sist-en-13200-4-2007>***ICS:**

91.040.10	Javne stavbe	Public buildings
97.200.10	Gledališka, odrska in studijska oprema ter delovne postaje	Theatre, stage and studio equipment
97.220.10	Športni objekti	Sports facilities

SIST EN 13200-4:2007**en**

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST EN 13200-4:2007

<https://standards.iteh.ai/catalog/standards/sist/4553067f-fa9f-4a1d-a297-ab560aa40d53/sist-en-13200-4-2007>

ICS 91.040.10; 97.200.10; 97.220.10

English Version

Spectator facilities - Part 4: Seats - Product characteristics

Installations pour spectateurs - Partie 4: Sièges -
Caractéristiques des produits

Zuschaueranlagen - Teil 4: Sitze - Produktmerkmale

This European Standard was approved by CEN on 28 August 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

<https://standards.iteh.ai/catalog/standards/sist/4553067f-fa9f-4a1d-a297-ab560aa40d53/sist-en-13200-4-2007>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Abbreviations	5
5 General requirements of construction	5
5.1 Seats	5
5.2 General requirements for fixing elements and fixing methods	6
5.2.1 General.....	6
5.2.2 Criteria for presentation of designs	7
5.2.3 Acceptance testing	7
6 Sampling and conditioning.....	7
6.1 Sampling.....	7
6.2 Conditioning.....	7
7 Characteristics of materials.....	7
7.1 General.....	7
7.2 Corrosion resistance	7
7.3 Resistance to weathering agents/stability to light	8
7.4 Temperature resistance	8
8 Strength and durability requirements.....	8
9 Test report	10
10 Seating numbers.....	11
11 Instruction for use	11
12 Marking	11
Annex A (informative) Temperature resistance	12
A.1 Temperature resistance	12
A.1.1 General.....	12
A.1.2 Low temperature test	12
A.1.3 High temperature test.....	12
Annex B (informative) Examples of seats.....	13
Annex C (informative) Ergonomy	15
C.1 Ergonomy	15
C.1.1 Anthropometric aspects and data.....	15
C.1.2 Design requirements	15
Bibliography	24

Foreword

This document (EN 13200-4:2006) has been prepared by Technical Committee CEN/TC 315 “Spectators facilities”, the secretariat of which is held by UNI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2007, and conflicting national standards shall be withdrawn at the latest by April 2007.

EN 13200 *Spectator facilities* consists of the following parts:

Part 1: Layout criteria for spectator viewing area — Specification

Part 3: Separating elements — Requirements

Part 4: Seats-product characteristics

Part 5: Telescopic stands

Part 6: Demountable (temporary) stands

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

<https://standards.iteh.ai/catalog/standards/sist/4553067f-fa9f-4a1d-a297-ab560aa40d53/sist-en-13200-4-2007>

1 Scope

This European Standard specifies the mechanical, physical and chemical product characteristics of fixed seating used in sports venues (indoor and outdoor) in the spectator viewing area (S.V.A.). It also specifies the criteria for fixing the seating to the structure.

These characteristics and criteria are determined in order to assure an adequate resistance to static and dynamic stresses and to atmospheric agents. This European Standard specifies comfort, functionality and safety requirements to prevent serious injury through normal functional use, as well as misuse that might reasonably be expected to occur. This European Standard does not include any fire behaviour or resistance requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12727, *Furniture — Ranked seating — Test methods and requirements for strength and durability*

EN 13200-1, *Spectator facilities — Part 1: Layout criteria for spectator viewing area — Specification*

ENV 581-2:2000, *Outdoor furniture — Seating and tables for camping, domestic and contract use — Part 2: Mechanical safety requirements and test methods for sampling*

EN ISO 527-2, *Plastics — Determination of tensile properties — Part 2: Test conditions for moulding and extrusion plastics (ISO 527-2:1993 including Corr. 1:1994)*

EN ISO 4892-2, *Plastics — Methods of exposure to laboratory light sources — Part 2: Xenon-arc lamps (ISO 4892-2:2006)*

ISO 105-A02, *Textiles — Tests for colour fastness — Part A02: Grey scale for assessing change in colour*

ISO 179-1:2000, *Plastics — Determination of Charpy impact properties — Part 1: Non-instrumented impact test (ISO 179-1:2000)*

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

seating place

space intended for a single spectator in a sitting position (see figures in Annex B)

3.2

seats

- bench, a continuous element, forming a raised seat level with respect to the footway (Figure B.1);
- low back seat, a shaped element or an assembly fixed to the step or on to a support. It has a backrest with a maximum height of 15 cm above the seat level and may be fitted with armrests (Figure B.2);

- high back seat, a shaped element or an assembly fixed to the step or on to a support. It has a backrest with a minimum height of 15 cm above the seat level and may be fitted with armrests (Figure B.3);
- tip-up seat, a seating place where in the seat elements automatically returns to the upright position on the departure of the occupant (Figure B.4)

3.3

fixing elements

elements for attaching the seat to the fixed support

3.4

fixing method

assembly of elements for attaching the support or the seats to a stand

3.5

seat numbering

means of identifying seat position

NOTE 1 The different types of seating places which are shown in the figures are only examples.

NOTE 2 For general terms relating to the structures of spectator facilities, see EN 13200-1.

4 Abbreviations

For the purposes of this document, the abbreviations in EN 13200-1 and the following apply.

Bse: dimension of the tread where seating places are (seating row depth);

F: depth of seats including the thickness of the back;

I: width of seats (minimum dimension for lateral boundaries of a single seating place);

E: distance between the foremost projection of one seat and the back of the seat in front of it (clearway);

S: height of seat back, including the thickness of the seat.

5 General requirements of construction

5.1 Seats

The seats shall comply with the following general requirements.

- a) it shall be so designed to not cause injury to the user. All parts of the seating place with which the user comes into contact, during the intended use, shall be so designed that physical injury and damage to spectator property are avoided. The following considerations are necessary:
 - the safety distance of accessible movable parts is addressed to EN 294 in any position during movement;
 - all accessible parts are without sharp edges/corners;
 - the edges of the seat, backrest and armrests which are in contact with the user when sitting, are rounded with recommended minimum 3 mm radius;
 - the ends of hollow components are closed or capped.

- b) all parts which are lubricated to assist sliding (greasing, lubricating etc.) shall be designed to protect users from lubricant stains when in normal use;
- c) seats shall be securely fixed to the steps or to the supports;
- d) the shape of the seats shall be such as to allow rain and water to drain and shall allow easy cleaning of it and of the underlying steps;
- e) if the components are made of different materials, they shall be compatible with each other;
- f) the seating place shall comply the minimum dimensions given in EN 13200-1;
- g) the recommended values are given in Table 1.

Table 1 — Recommended dimensional criteria for seats

Seat type	F (mm)	I (mm)	S (mm)	Row depth (B_{se}) (mm)	
				min	rec
Bench	300	0	0	700	800
Seat with low back	400	500	< 150	700	800
Seat with high back	400	500	> 150	700	800

5.2 General requirements for fixing elements and fixing methods

5.2.1 General

The fixing of the seats shall comply with the following requirements:

- a) the fixing elements of the seats shall withstand the forces generated during the tests described in EN 12727;
- b) it shall not be possible to remove the seats without the use of a special tool;
- c) the fixing methods shall be compatible with the supporting structure;
- d) the metal elements making up the fixing elements and fixing methods shall be protected against corrosion (see 7.2);
- e) regarding materials, see Clause 6.

5.2.2 Criteria for presentation of designs

The design including plans, sections and elevations, and details of the seat, of the fixed support and of the fixing elements, at an appropriate scale, shall include the declaration of conformity to this European Standard and a report of the static tests on the seat, and the fixing support structure.

5.2.3 Acceptance testing

An independent agent shall ascertain the compliance between the design and the finished product.

The agent is entitled to accept the declaration of conformity and the calculations contained in the design or to carry out additional checks.

6 Sampling and conditioning

6.1 Sampling

The minimum number of samples to be tested shall be two.

The samples to be tested shall always be inspected before and after each test, any significant changes that have taken place shall be recorded.

6.2 Conditioning

At least two weeks in normal conditions, 23/50 according to ISO 554, shall have elapsed between manufacturing (or assembling) and testing in the case of glued joints in timber and the like.

The tests shall be carried out in normal ambient conditions but, upon agreement, tests may be carried out in special ambient conditions and these shall be recorded in the test report.

The test samples of other materials shall be contained in normal conditions, 23/50 according to ISO 554 for at least 72 h.

7 Characteristics of materials

7.1 General

Assessment of the characteristics of materials used in the seating assembly, shall be carried out on the finished products but might be carried out on test specimens derived from it, after conditioning according 6.2.

The components of seating assembly shall comply with the following requirements.

All components shall comply with the national regulations regarding fire behaviour.

7.2 Corrosion resistance

All metal components of the seating and the fixing elements shall be corrosion resistant.

This requirement is met when, after testing according with ISO 9227 for:

- 500 h of exposure for outdoor use;
- 200 h of exposure for indoor use.

No visual defects are to be noticeable; compliance is checked by visual inspection.

7.3 Resistance to weathering agents/stability to light

Plastic components of the seating shall be exposed to a xenon arc lamp according to EN ISO 4892-2.

They shall be irradiated for a total energy of 8,3 GJ/m² in the wavelength range of 295 nm to 3000 nm.

NOTE In the test conditions of xenon arc lamp described in EN ISO 4892-2 method A, this energy value is achieved with an irradiation period of 2 300 h when a spectral irradiance of 0,50 W/m² (at 340 nm) is selected.

The test chamber conditions are the following:

- black panel temperature: 63 °C ± 3 °C;
- relative humidity: 65 % ± 5 %;
- 102 min of light;
- 18 min of light and water spray.

After exposure, the test specimens shall not show any visual defects on the exposed surface.

The assessment of colour variation rating shall be according to ISO 105-A02, grey scale.

The minimum rating shall be agreed between client and supplier.

Alternative measurements can be performed such as:

- colour variation according to ISO 7724 parts 1, 2 and 3 (Lab colour parameters);
- gloss variation according to EN ISO 2813.

When tested according to EN ISO 527-2, the exposed specimen shall have a maximum yield strain variation from the unexposed specimen of 30 %.

When tested according to EN ISO 179-1:2000, test method 1 e A, the exposed specimen shall have a maximum Charpy impact strength variation from the unexposed specimen of 30 %.

7.4 Temperature resistance

See Annex A.

8 Strength and durability requirements

Seats shall be tested according to EN 12727 to assess the mechanical resistance. Several loads and cycles can be performed according to 4 different levels of severity (1, 2, 3 and 4). At the end of the tests, there shall be no damage or deformation that will affect the safe use of the seating and the functions shall be maintained.

NOTE It is recommended to perform tests according to level 4 of EN 12727.

Table 2 — List of test methods and requirements for strength and durability according to EN 12727

Test	Loading	1	2	3	4
Type of use		Light	Moderate	General	Severe
Seat static load)	force N	1 300	1 600	2 000	2 000
)	10 times				
) combined					
Back static load)	force N	560	760	760	760
)	10 times				
Horizontal static load to back	force N	-	-	760	760
Vertical static test on back	force N	600	600	900	900
Arm sideways static load	force N	400	600	900	1 000
Arm downwards static load	force N	800	900	1 000	1 000
Seat fatigue test)	cycles	50 000	100 000	150 000	200 000
)	Seat load 950 N				
) combined					
Back fatigue test)	Back load				
)					
)	330 N				
Seat front edge fatigue test	cycles	50 000	100 000	150 000	200 000
	Seat load 950 N				