



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment to be used
in the 40 GHz to 246 GHz frequency range;
Part 2: Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

Reference

REN/ERM-TG28-502

Keywords

Harmonized standard, radio, regulation, SRD,
testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 4 |
| Foreword..... | 4 |
| Modal verbs terminology..... | 5 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 2.1 Normative references | 7 |
| 2.2 Informative references..... | 7 |
| 3 Definitions, symbols and abbreviations | 7 |
| 3.1 Definitions..... | 7 |
| 3.2 Symbols..... | 7 |
| 3.3 Abbreviations | 7 |
| 4 Technical requirements specifications | 8 |
| 4.1 Environmental profile..... | 8 |
| 4.2 Conformance requirements | 8 |
| 4.2.1 Transmitter requirements | 8 |
| 4.2.1.1 Spectral power density | 8 |
| 4.2.1.2 RF output power..... | 8 |
| 4.2.1.3 Permitted range of operating frequencies..... | 8 |
| 4.2.1.4 Out-of-band emissions | 8 |
| 4.2.1.5 Unwanted emissions in the spurious domain..... | 8 |
| 4.2.2 Receiver requirements | 8 |
| 4.2.2.1 Unwanted emissions..... | 8 |
| 5 Testing for compliance with technical requirements..... | 9 |
| 5.1 Description of testing for compliance with technical requirements | 9 |
| 5.1.1 Environmental conditions for testing..... | 9 |
| 5.1.1.1 Normal and extreme test-conditions..... | 9 |
| 5.1.1.2 Test power source | 9 |
| 5.1.2 Choice of samples for test suites..... | 9 |
| 5.2 Interpretation of the measurement results | 9 |
| 5.3 Essential transmitter test suites..... | 9 |
| 5.3.1 Spectral power density..... | 9 |
| 5.3.2 RF output power | 10 |
| 5.3.3 Permitted range of operation frequencies | 10 |
| 5.3.4 Out-of-band emissions..... | 10 |
| 5.3.5 Unwanted emissions in the spurious domain | 10 |
| 5.4 Essential receiver test suites | 10 |
| 5.4.1 unwanted radiated components | 10 |
| Annex A (normative): HS Requirements and conformance Test specifications Table (HS-RTT)..... | 11 |
| Annex B (informative): Void | 13 |
| Annex C (informative): Bibliography..... | 14 |
| History | 15 |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is a new standard that takes advantage of technical developments within the SRD industry. In particular this includes the development in technologies which makes applications in the higher frequency range possible.

The present document has been produced by ETSI in response to a mandate M/284 issued from the European Commission under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.9].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 2 of a multi-part deliverable covering Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 40 GHz to 246 GHz frequency range, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

| Proposed national transposition dates | |
|--|---------------------------------|
| Date of latest announcement of this EN (doa): | 3 months after ETSI publication |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 6 months after doa |
| Date of withdrawal of any conflicting National Standard (dow): | 18 months after doa |

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.4].

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/01f1bd20-a0c9-4cc0-a7d1-cb52d60a03c6/etsi-en-305-550-2-v1.2.1-2014-10>

1 Scope

The present document applies to the following Short Range Device major equipment types:

- Generic Short Range Devices, including alarms, telecommand, telemetry, data transmission in general, etc.

These radio equipment types are capable of operating in the frequency bands within the 40 GHz to 246 GHz range as specified in table 1:

- either with a Radio Frequency (RF) output connection and dedicated antenna or with an integral antenna;
- for all types of modulation.

Table 1 shows a list of the frequency bands as designated in the CEPT/ERC Recommendation 70-03 [i.3] as known at the date of publication of the present document.

NOTE 1: Table 1 represents the most widely implemented position within the CEPT countries [i.3], but it should not be assumed that all designated bands are available in all countries. It is also foreseen that these frequencies may be implemented in [i.6], [i.7] and [i.8] in the future.

Table 1: Short Range Devices within the 40 GHz to 246 GHz frequency range

| Frequency Bands | Applications | Notes |
|----------------------|------------------|-------|
| 57 GHz to 64 GHz | Non-specific SRD | |
| 61,0 GHz to 61,5 GHz | Non-specific SRD | |
| 122 GHz to 123 GHz | Non-specific SRD | |
| 244 GHz to 246 GHz | Non-specific SRD | |

NOTE 2: In addition, it should be noted that other frequency bands may be available in a country within the frequency range 40 GHz to 246 GHz covered by the present document. the CEPT/ERC Recommendation 70-03 [i.3] as implemented through National Radio Interfaces (NRI) and additional NRI as relevant.

NOTE 3: On non-harmonized parameters, national administrations may impose certain conditions such as the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated power, duty cycle, and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of an individual or general licence, or as a condition for the issuing of Individual Rights for use of spectrum or General Authorization, or as a condition for use "under licence exemption" as it is in most cases for Short Range Devices.

The present document covers fixed stations, mobile stations and portable stations.

NOTE 4: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 305 550-1 (V1.2.1) (06-2014): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 40 GHz to 246 GHz frequency range; Part 1: Technical characteristics and test methods".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] CEPT/ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.4] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.5] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] European Commission Decision (2006/771/EC) of 9 November 2006 on harmonization of the radio spectrum for use by short-range devices.
- [i.7] European Commission Decision 2013/752/EU of 11 December 2013 (amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2005/928/EC).
- [i.8] CEPT/ERC Recommendation 74-01: "Unwanted emissions in the spurious domain", Hradec Kralove, Cardiff 2011.
- [i.9] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.2] and EN 305 550-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in EN 305 550-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in EN 305 550-1 [1] apply.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.1 Transmitter requirements

4.2.1.1 Spectral power density

The spectral power density, as defined in EN 305 550-1 [1], clause 7.1.1, shall not exceed the limits in EN 305 550-1 [1], clause 7.1.2, Table 9.

This requirement applies to transmitters operating in the 57 GHz to 66 GHz frequency range.

4.2.1.2 RF output power

The RF output power, as defined in EN 305 550-1 [1], clause 7.2.1, shall not exceed the limits in EN 305 550-1 [1], clause 7.2.2, Table 10.

4.2.1.3 Permitted range of operating frequencies

The permitted range of operating frequencies, as defined in EN 305 550-1 [1], clause 7.3.1, shall not exceed the limits in EN 305 550-1 [1], clause 7.3.4.

This requirement applies to all transmitters.

4.2.1.4 Out-of-band emissions

The Out-of-band emissions in the Out-of-band domain, as defined in EN 305 550-1 [1], clause 7.4.1, shall not exceed the limits in EN 305 550-1 [1], clause 7.4.4, table 13.

This requirement applies to all transmitters.

4.2.1.5 Unwanted emissions in the spurious domain

The unwanted emissions in the spurious domain, as defined in EN 305 550-1 [1], clause 7.5.1, shall not exceed the limits in EN 305 550-1 [1], clause 7.5.4, table 14.

This requirement applies to all transmitters.

4.2.2 Receiver requirements

4.2.2.1 Unwanted emissions

The unwanted emissions as defined in EN 305 550-1 [1], clause 8.1.1, shall not exceed the limits in EN 305 550-1 [1], clause 8.1.3.

5 Testing for compliance with technical requirements

5.1 Description of testing for compliance with technical requirements

5.1.1 Environmental conditions for testing

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile.

Where technical performance varies subject to environmental conditions, tests shall be carried out under a sufficient variety of environmental conditions (within the boundary limits of the declared operational environmental profile) to give confidence of compliance for the affected technical requirements.

5.1.1.1 Normal and extreme test-conditions

The test procedures shall be as specified in EN 305 550-1 [1], clauses 5.2 to 5.4.

5.1.1.2 Test power source

The test power source shall meet the requirements of EN 305 550-1 [1], clause 5.2.

5.1.2 Choice of samples for test suites

Measurement shall be performed, according to the present document, on samples of equipment defined in EN 305 550-1 [1], clause 4.2.1.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the values in clause 4.8, table 4 of EN 305 550-1 [1].

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with the principles contained within TR 100 028 [i.5] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

The particular expansion factor used for the evaluation of the measurement uncertainty shall be stated.

5.3 Essential transmitter test suites

5.3.1 Spectral power density

The test specified in EN 305 550-1 [1], clause 7.1.3 shall be carried out.

This test suite applies to all transmitters.