

## SLOVENSKI STANDARD SIST EN IEC 60268-4:2019

01-maj-2019

Nadomešča:

SIST EN 60268-4:2014

Elektroakustične naprave - 4. del: Mikrofoni (IEC 60268-4:2018)

Sound system equipment - Part 4: Microphones (IEC 60268-4:2018)

Elektroakustische Geräte - Teil 4: Mikrofone (IEC 60268-4:2018)

iTeh STANDARD PREVIEW

Equipements pour systèmes électroacoustiques - Partie 4: Microphones (IEC 60268-4:2018) (standards.iteh.ai)

SIST EN IEC 60268-4:2019

Ta slovenski standard je istoveten zbystan EN/IEC 60268-4:2018-8342-

755106ef8246/sist-en-iec-60268-4-2019

ICS:

33.160.50 Pribor Accessories

SIST EN IEC 60268-4:2019 en,fr,de

**SIST EN IEC 60268-4:2019** 

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN IEC 60268-4:2019

https://standards.iteh.ai/catalog/standards/sist/907e5463-731a-4605-8342-755106ef8246/sist-en-iec-60268-4-2019

## EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

**EN IEC 60268-4** 

November 2018

ICS 33.160.50

Supersedes EN 60268-4:2014

### **English Version**

## Sound system equipment - Part 4: Microphones (IEC 60268-4:2018)

Equipements pour systèmes électroacoustiques - Partie 4: Microphones (IEC 60268-4:2018) Elektroakustische Geräte - Teil 4: Mikrofone (IEC 60268-4:2018)

This European Standard was approved by CENELEC on 2018-10-17. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

(standards.iteh.ai)

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom a Catalog standards/sist/907e5463-731a-4605-8342-

755106ef8246/sist-en-iec-60268-4-2019



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

## EN IEC 60268-4:2018 (E)

## **European foreword**

The text of document 100/2992/CDV, future edition 6 of IEC 60268-4, prepared by IEC/TC 100 "Audio, video and multimedia systems and equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60268-4:2018.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2019-07-17 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2021-10-17

This document supersedes EN 60268-4:2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

## **Endorsement notice**

SIST EN IEC 60268-4:2019

https://standards.iteh.ai/catalog/standards/sist/907e5463-731a-4605-8342-

The text of the International Standard IEC 60268-4:2018 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

Harmonized as EN 55022:2010 (modified)	NOTE	CISPR 22:2008
Harmonized as EN 60065:2014 (modified)	NOTE	IEC 60065:2014
Harmonized as EN 60958-4:2016 (series)	NOTE	IEC 60958-4:2016 (series)
Harmonized as EN 61000-3-2:2014 (not modified	NOTE	IEC 61000-3-2:2014
Harmonized as EN 61000-3-3:2013 (not modified	NOTE	IEC 61000-3-3:2013
Harmonized as EN 61606 (series)	NOTE	IEC 61606 (series)
Harmonized as EN 61672-1:2013 (not modified)	NOTE	IEC 61672-1:2013

## Annex ZA

(normative)

## Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: <a href="https://www.cenelec.eu">www.cenelec.eu</a>.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
CISPR 35 (mod)	2016 iT	Electromagnetic compatibility of multimedia equipment Immunity requirements P	EN 55035	2017
IEC 60268-1	1985	Sound system equipment. Part 1: General	HD 483.1 S2	1989
+ A1	1988	(stanuarus.iten.ai)	-	-
+ A2	1988	SIST EN IEC 60268-4:2019	-	-
IEC 60268-2	1987 <sup>sta</sup>	Sound system equipment. Part 2: Explanation of general terms and calculation methods	<sup>83</sup> HD 483.2 S2	1993
+ A1	1991		-	-
IEC 60268-3	2013	Sound system equipment - Part 3: Amplifiers	EN 60268-3	2013
IEC 60268-5	2003	Sound system equipment - Part 5: Loudspeakers	EN 60268-5	2003
+ A1	2007		+ A1	2009
IEC 60268-11	1987	Sound system equipment. Part 11: Application of connectors for the interconnection of sound system components	HD 483.11 S3	1993
+ A1	1989		-	-
+ A2	1991		-	-
IEC 60268-12	1987	Sound system equipment. Part 12: Application of connectors for broadcast and similar use	EN 60268-12	1995
+ A1	1991		-	-
+ A2	1994		+ A2	1995
IEC 61000-4-2	2008	Electromagnetic compatibility (EMC) - Part 4- 2: Testing and measurement techniques - Electrostatic discharge immunity test	EN 61000-4-2	2009

## EN IEC 60268-4:2018 (E)

IEC 61000-4-3	2006	Electromagnetic compatibility (EMC) - Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test	EN 61000-4-3	2006
+ A1	2007		+ A1	2008
+ A2	2010		+ A2	2010
IEC 61000-4-4	2012	Electromagnetic compatibility (EMC) - Part 4- 4: Testing and measurement techniques - Electrical fast transient/burst immunity test	EN 61000-4-4	2012
IEC 61000-4-6	2013	Electromagnetic compatibility (EMC) - Part 4- 6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields	EN 61000-4-6	2014
IEC 61000-4-8	2009	Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test	EN 61000-4-8	2010
IEC 61000-4-16	2015	Electromagnetic compatibility (EMC) - Part 4-16: Testing and measurement techniques - Test for immunity to conducted, common mode disturbances in the frequency range 0 Hz to 150 kHz	EN 61000-4-16	2016
IEC 61000-4-17	1999 iT	Electromagnetic compatibility (EMC) - Part 4- 17: Testing and measurement techniques - Ripple on d.c. input power port immunity test	EN 61000-4-17	1999
+ A1	2001	(standards.iteh.ai)	+ A1	2004
+ A2	2008	CICT EN IEC (00(0 4:0010	+ A2	2009
IEC 61260-1	1 <b>201</b> <i>A</i> st	SIST EN IEC 60268-4:2019 an Electroacoustics/siOctave-band and fractional- octave-band filters is Part 1: Specifications	83 <b>⊑</b> № 61260-1	2014
IEC 61938	2013	Multimedia systems - Guide to the recommended characteristics of analogue interfaces to achieve interoperability	-	-
ITU-T Recommendation P.51	-	Artificial mouth	-	-
EN 55103-2	2009	Electromagnetic compatibility - Product family standard for audio, video, audio-visual and entertainment lighting control apparatus for professional use - Part 2: Immunity	EN 55103-2	2009
EN 300 422-2 V1.3.1	2011	Electromagnetic compatibility and radio spectrum matters (ERM) - Wireless microphones in the 25 MHz to 3 GHz frequency range - Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive	EN 300 422-2 V1.3.1	2011



IEC 60268-4

Edition 6.0 2018-09

## INTERNATIONAL STANDARD

# Sound system equipmen STANDARD PREVIEW Part 4: Microphones (standards.iteh.ai)

<u>SIST EN IEC 60268-4:2019</u> https://standards.iteh.ai/catalog/standards/sist/907e5463-731a-4605-8342-755106ef8246/sist-en-iec-60268-4-2019

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.160.50 ISBN 978-2-8322-5955-9

Warning! Make sure that you obtained this publication from an authorized distributor.

## CONTENTS

FC	REWO	RD	6
1	Scop	e	8
2	Norm	native references	8
3	Term	s and definitions	9
4	Gene	eral conditions	10
	4.1	General	10
	4.2	Measurement conditions	10
	4.2.1	General	10
	4.2.2	Rated conditions	11
5	Parti	cular conditions	12
	5.1	Pre-conditioning	12
	5.2	Sound source	12
	5.3	Measurement of sound pressure	12
	5.4	Voltage measuring system	
	5.5	Acoustical environment	
	5.5.1		
	5.5.2	TALOTANDADD DDEVIEW	13
	5.5.3		
	5.5.4	Microphone coupled to a sound source by means of a small cavity coupler	15
	5.6	Methods of measuring frequency response	
	5.6.1	SIST EN 1EC 6026x-42019	15
	5.6.2	nitips://standards.iten.avcatalog/standards/sist/90/e3463-731a-4605-8342- Calibration methods/06e/8246/sist-en-ice-60268-4-2019	16
	5.7	Overall accuracy	
	5.8	Graphical presentation of results	16
6	Туре	description (acoustical behaviour)	17
	6.1	Principle of the transducer	17
	6.2	Type of microphone	17
	6.3	Type of directional response characteristics	17
	6.4	Application	
7	Term	inals and controls	
	7.1	Marking	
	7.2	Connectors and electrical interface values	
8		rence point and axis	
	8.1	Reference point	
_	8.2	Reference axis	
9		d power supply	
	9.1	Characteristics to be specified	
	9.2	Method of measurement	
10		rical impedance	
	10.1	Internal impedance	
	10.1.	•	
	10.1.		
	10.2	Rated impedance	
	10.3	Rated minimum permitted load impedance	19

11.1 General.       19         11.2 Sensitivities with respect to acoustical environment       20         11.2.1 Free-field sensitivity       20         11.2.2 Diffuse-field sensitivity       21         11.2.3 Close-talking and near-field sensitivity       21         11.2.4 Pressure sensitivity       22         11.3 Rated sensitivity       22         12 Response       22         12.1 Frequency response       22         12.1.1 Characteristic to be specified       22         12.1.2 Method of measurement       23         12.2 Effective frequency range       23         12.2.2 Method of measurement       23         12.2 Effective frequency range       23         13.1 Directional characteristic to be specified       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       23         13.1.2 Methods of measurement       23         13.2.1 Characteristic to be specified       23         13.2.2 In Characteristic to be specified       25         13.2.2 Method of measurement       25         13.2.2 Method of measurement       25         14.2 Total harmonic distortion       25         14.3 Ceneral       25         14.2 Total h	11	Sens	itivity	/	19
11.2.1       Free-field sensitivity       20         11.2.2       Diffuse-field sensitivity       21         11.2.3       Close-talking and near-field sensitivity       21         11.2.4       Pressure sensitivity       22         12. Response       22         12.1       Frequency response       22         12.1.1       Characteristic to be specified       22         12.1.2       Method of measurement       23         12.2.1       Method of measurement       23         12.2.2       Method of measurement       23         12.2.1       Characteristic to be specified       23         12.2.2       Method of measurement       23         13.1       Directional pattern       23         13.1.1       Characteristic to be specified       23         13.1.2       Methods of measurement       23         13.2.1       Characteristic to be specified       23         13.1.2       Method of measurement       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement       25         14.2       Total harmonic distortion       25         14.2.1       Characteristic to be specified		11.1	Gen	eral	19
11.2.2 Diffuse-field sensitivity       21         11.2.3 Close-talking and near-field sensitivity       21         11.2.4 Pressure sensitivity       22         11.3 Rated sensitivity       22         12 Response       22         12.1 Frequency response       22         12.1.1 Characteristic to be specified       22         12.1.2 Method of measurement       23         12.2 Effective frequency range       23         12.2.2 Effective frequency range       23         12.2.2 Method of measurement       23         12.2.2 Method of measurement       23         13 Directional pattern       23         13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       25         13.2 Directivity index       (§ 2 and 2 feb. 10 feb.		11.2	Sen	sitivities with respect to acoustical environment	20
11.2.3       Close-talking and near-field sensitivity       21         11.2.4       Pressure sensitivity       22         11.3       Rated sensitivity       22         12       Response       22         12.1       Frequency response       22         12.1.1       Characteristic to be specified       22         12.1.2       Method of measurement       23         12.2       Effective frequency range       23         12.2.1       Characteristic to be specified       23         12.2.2       Method of measurement       23         13.1       Directional characteristics       23         13.1.1       Characteristic to be specified       23         13.1.2       Methods of measurement       24         13.1.3       Graphical presentation of results       25         13.2.2       Intentity index       (standards.icell.ai)       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement       25         14.1       General       75510ccR246/sisten ice 60268-1-2019       25     <		11.2.	1	Free-field sensitivity	20
11.2.4 Pressure sensitivity       22         11.3 Rated sensitivity       22         22 Response       22         12.1 Frequency response       22         12.1.1 Characteristic to be specified       22         12.1.2 Method of measurement       23         12.1.3 Graphical presentation of results       23         12.2 Effective frequency range       23         12.2.1 Characteristic to be specified       23         13.1.2 Directional characteristics       23         13.1 Directional pattern       23         13.1.2 Methods of measurement       23         13.1.3 Graphical presentation of results       25         13.2.2 Directivity index       (\$100.000.000.000.000.000.000.000.000.000		11.2.	2	Diffuse-field sensitivity	21
11.2.4 Pressure sensitivity       22         11.3 Rated sensitivity       22         22 Response       22         12.1 Frequency response       22         12.1.1 Characteristic to be specified       22         12.1.2 Method of measurement       23         12.1.3 Graphical presentation of results       23         12.2 Effective frequency range       23         12.2.1 Characteristic to be specified       23         13.1.2 Directional characteristics       23         13.1 Directional pattern       23         13.1.2 Methods of measurement       23         13.1.3 Graphical presentation of results       25         13.2.2 Directivity index       (\$100.000.000.000.000.000.000.000.000.000		11.2.	3	Close-talking and near-field sensitivity	21
12.1 Frequency response       22         12.1.1 Characteristic to be specified       22         12.1.2 Method of measurement       23         12.1.3 Graphical presentation of results       23         12.2 Effective frequency range       23         12.2.1 Characteristic to be specified       23         12.2.2 Method of measurement       23         13.1 Directional characteristics       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results       24         13.2 Directivity index       (\$\frac{2\text{standards.iteh.ai}}{2\text{standards.iteh.ai}}\$       25         13.2.1 Characteristic to be specified       25         13.2.2 Method of measurement In Inc.0064.4300       25         14.3 Amplitude non-linearity usk whatataky suntants standards standard		11.2.	4		
12.1 Frequency response       22         12.1.1 Characteristic to be specified       22         12.1.2 Method of measurement       23         12.1.3 Graphical presentation of results       23         12.2 Effective frequency range       23         12.2.1 Characteristic to be specified       23         13.2.2 Method of measurement       23         13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results DPREVIEW       24         13.2 Directivity index       (standards.itch.at)         13.2 Directivity index       (standards.itch.at)         13.2 Directivity index       (standards.itch.at)         25       13.2 Directivity index       (standards.itch.at)         26       13.2 Directivity index       (standards.itch.at)         27       14.2 D		11.3	Rate	ed sensitivity	22
12.1.1       Characteristic to be specified       22         12.1.2       Method of measurement       23         12.1.3       Graphical presentation of results       23         12.2       Effective frequency range       23         12.2.1       Characteristic to be specified       23         12.2.2       Method of measurement       23         13       Directional pattern       23         13.1.1       Characteristic to be specified       23         13.1.2       Methods of measurement       24         13.1.3       Graphical presentation of results       PREVIEW         24       13.1.3       Graphical presentation of results       PREVIEW         25       13.2       Methods of measurement       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement       25         14.3       Amplitude non-linearity wheth activative survives with section of 26/24/24/24/24/24/24/24/24/24/24/24/24/24/	12	Resp	onse		22
12.1.1       Characteristic to be specified       22         12.1.2       Method of measurement       23         12.1.3       Graphical presentation of results       23         12.2       Effective frequency range       23         12.2.1       Characteristic to be specified       23         12.2.2       Method of measurement       23         13       Directional pattern       23         13.1.1       Characteristic to be specified       23         13.1.2       Methods of measurement       24         13.1.3       Graphical presentation of results       PREVIEW         24       13.1.3       Graphical presentation of results       PREVIEW         25       13.2       Methods of measurement       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement       25         14.3       Amplitude non-linearity wheth activative survives with section of 26/24/24/24/24/24/24/24/24/24/24/24/24/24/		12.1	Fred	uency response	22
12.1.2       Method of measurement.       23         12.1.3       Graphical presentation of results       23         12.2       Effective frequency range.       23         12.2.1       Characteristic be specified       23         12.2.2       Method of measurement.       23         13.1       Directional pattern.       23         13.1.1       Characteristic be specified       23         13.1.2       Methods of measurement.       24         13.1.3       Graphical presentation of results       25         13.2       Directivity index       52         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement.       25         13.2.2       Method of measurement.       25         14.1       General.       25         14.2       Total harmonic distortion       25         14.2       Total harmonic distortion       25         14.2.1       Characteristic to be specified       25         14.2.2       Method of measurement       26         14.3.1       Characteristic to be specified       26         14.3.2       Method of measurement       26         14.4.1       Characteristic to be		12.1.		, ,	
12.1.3       Graphical presentation of results       23         12.2       Effective frequency range       23         12.2.1       Characteristic to be specified       23         12.2.2       Method of measurement       23         13       Directional characteristics       23         13.1.1       Directional pattern       23         13.1.2       Methods of measurement       24         13.1.3       Graphical presentation of results DPREVIEW       25         13.2       Directivity index       (\$100 or 100 or		12.1.	2	•	
12.2 Effective frequency range       23         12.2.1 Characteristic to be specified       23         12.2.2 Method of measurement       23         13 Directional characteristics       23         13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results       25         13.2 Directivity index       (\$1 and ard \$1.00 pt. 10		12.1.	3		
12.2.1 Characteristic to be specified       23         12.2.2 Method of measurement       23         13 Directional characteristics       23         13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results D PREVIEW       25         13.2 Directivity index       (\$\frac{1}{2}\text{andards.itch.aii}\$)       25         13.2.1 Characteristic to be specified       25         13.2.2 Method of measurement. INITIC 60/68-4/200       25         14.3 Amplitude non-linearity als inhait antigorandards stromatics and colors. 240:584-2019       25         14.1 General       755106cR246/sist-en-rec-60268-4-2019       25         14.2 Total harmonic distortion       25         14.2.1 Characteristic to be specified       25         14.2.2 Method of measurement       26         14.3 Harmonic distortion of the nth order (n = 2, 3,)       26         14.3.1 Characteristic to be specified       26         14.4.2 Method of measurement       26         14.4 Difference frequency distortion of second order       27         14.4.2 Method of measurement       27         15.1 Rated maximum permissible peak sound pressure       28         15.2 O				·	
12.2.2 Method of measurement       23         13 Directional characteristics       23         13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results       25         13.2 Directivity index       (\$1.2.2.2.4.2.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0				, , ,	
13 Directional characteristics       23         13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results       25         13.2 Directivity index       25         13.2.1 Characteristic to be specified       25         13.2.2 Method of measurement       25         14 Amplitude non-linearity and sitch aicatalog standards sist 2076 5463-731a-4605-8342-       25         14.1 General       755100cf8246 standards sist 2076-5463-731a-4605-8342-       25         14.2 Total harmonic distortion       25         14.2 Total harmonic distortion       25         14.2.1 Characteristic to be specified       25         14.3 Harmonic distortion of the nth order (n = 2, 3,)       26         14.3.1 Characteristic to be specified       26         14.3.2 Method of measurement       26         14.4 Difference frequency distortion of second order       27         14.4.2 Method of measurement       27         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28					
13.1 Directional pattern       23         13.1.1 Characteristic to be specified       23         13.1.2 Methods of measurement       24         13.1.3 Graphical presentation of results       25         13.2 Directivity index       5         13.2.1 Characteristic to be specified       25         13.2.2 Method of measurement. FM ISC 60768-43049       25         14 Amplitude non-linearity wis itch nicatologistandark sixt 907c 5463-731a-4605-8342       25         14.1 General       755100ct8246/sist-on-oc-60268-4-2019       25         14.2 Total harmonic distortion       25         14.2.1 Characteristic to be specified       25         14.3.2 Method of measurement       26         14.3.1 Characteristic to be specified       26         14.3.2 Method of measurement       26         14.4 Difference frequency distortion of second order       27         14.4.1 Characteristic to be specified       27         14.4.2 Method of measurement       27         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16. Balance       28         16.1 Balance of the microphone out	13				
13.1.1       Characteristic to be specified       23         13.1.2       Methods of measurement       24         13.1.3       Graphical presentation of results       25         13.2       Directivity index       (standards.iteh.at)       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement.       25         13.2.2       Method of measurement.       25         14. Amplitude non-linearity-wix scharctalg/stardar/s/sit/90763463-7310-4605-8342       25         14.1       General.       755106ef8246/sit-en-icc-60268-4-2019       25         14.2       Total harmonic distortion       25         14.2.1       Characteristic to be specified       25         14.2.2       Method of measurement.       26         14.3.1       Characteristic to be specified       26         14.3.2       Method of measurement.       26         14.4.1       Characteristic to be specified       27         14.4.2       Method of measurement.       27         15.1       Rated maximum permissible peak sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement.       28					
13.1.2       Methods of measurement       24         13.1.3       Graphical presentation of results       25         13.2       Directivity index (standards.itch.ai)       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement.EN.IEC 60268.4.2019       25         14       Amplitude non-linearity ards.ich.ai coatog/standards/six/90765463-731a.4605-8342       25         14.1       General		_		·	
13.2       Directivity index       (standards, itch.ai)       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement in Inc 60268 42019       25         14       Amplitude non-linearity and include standards six 907x5463-731a-4605-8342       25         14.1       General.       755106c8246/sist-en-icc-60268-4-2019       25         14.2       Total harmonic distortion       25         14.2.1       Characteristic to be specified       25         14.2.2       Method of measurement.       26         14.3.1       Characteristic to be specified       26         14.3.2       Method of measurement       26         14.4       Difference frequency distortion of second order       27         14.4.1       Characteristic to be specified       27         14.4.2       Method of measurement       27         15       Limiting characteristics       28         15.1       Rated maximum permissible peak sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16       Balance       28         16.1       Balance under working conditions       29				•	
13.2       Directivity index       (standards, itch.ai)       25         13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement in Inc 60268 42019       25         14       Amplitude non-linearity and include standards six 907x5463-731a-4605-8342       25         14.1       General.       755106c8246/sist-en-icc-60268-4-2019       25         14.2       Total harmonic distortion       25         14.2.1       Characteristic to be specified       25         14.2.2       Method of measurement.       26         14.3.1       Characteristic to be specified       26         14.3.2       Method of measurement       26         14.4       Difference frequency distortion of second order       27         14.4.1       Characteristic to be specified       27         14.4.2       Method of measurement       27         15       Limiting characteristics       28         15.1       Rated maximum permissible peak sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16       Balance       28         16.1       Balance under working conditions       29		_		Graphical presentation of results PREVIEW	25
13.2.1       Characteristic to be specified       25         13.2.2       Method of measurement. EN IEG 60268-42009       25         14       Amplitude non-linearity and submicatohystandards/stx/90763461-731a-4605-8342       25         14.1       General				ctivity index (standards itah ai)	25
13.2.2       Method of measurement. EN IEC 60368-43009.       25         14       Amplitude non-linearity wish includes and wish strong 755463-73 Ja-4605-8342.       25         14.1       General.       755106c8246 sist-en-icc-60268-4-2019       25         14.2       Total harmonic distortion.       25         14.2.1       Characteristic to be specified.       25         14.2.2       Method of measurement.       26         14.3       Harmonic distortion of the nth order (n = 2, 3,)       26         14.3.1       Characteristic to be specified.       26         14.3.2       Method of measurement.       26         14.4       Difference frequency distortion of second order.       27         14.4.1       Characteristic to be specified.       27         14.4.2       Method of measurement.       27         15       Limiting characteristics.       28         15.1       Rated maximum permissible peak sound pressure.       28         15.2.1       Characteristic to be specified.       28         15.2.2       Method of measurement.       28         16.1       Balance.       28         16.2       Balance under working conditions.       29         17.1       Characteristic to be specified.		13.2	1	Characteristic to be specified	25
14 Amplitude non-linearity and stehal/catalog/standards/sixt/907c5463-731a-4605-8342       25         14.1 General       755106cR246/sixt-en-icc-60268-4-2019       25         14.2 Total harmonic distortion       25         14.2.1 Characteristic to be specified       25         14.2.2 Method of measurement       26         14.3 Harmonic distortion of the nth order (n = 2, 3,)       26         14.3.1 Characteristic to be specified       26         14.3.2 Method of measurement       26         14.4 Difference frequency distortion of second order       27         14.4.1 Characteristic to be specified       27         14.4.2 Method of measurement       27         15 Limiting characteristics       28         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16.1 Balance       28         16.2 Balance under working conditions       29         17.1 Characteristic to be specified       29         17.2 Method of measurement       29         18 Ambient conditions       30		_		·	
14.1 General       755106et8246/sist-en-icc-60268-4-2019       25         14.2 Total harmonic distortion       25         14.2.1 Characteristic to be specified       25         14.2.2 Method of measurement       26         14.3 Harmonic distortion of the nth order (n = 2, 3,)       26         14.3.1 Characteristic to be specified       26         14.3.2 Method of measurement       26         14.4 Difference frequency distortion of second order       27         14.4.1 Characteristic to be specified       27         14.4.2 Method of measurement       27         15 Limiting characteristics       28         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16.1 Balance       28         16.2 Balance under working conditions       29         17.1 Characteristic to be specified       29         17.2 Method of measurement       29         17.2 Method of measurement       29         18 Ambient conditions       30	11	_			
14.2 Total harmonic distortion       25         14.2.1 Characteristic to be specified       25         14.2.2 Method of measurement       26         14.3 Harmonic distortion of the nth order (n = 2, 3,)       26         14.3.1 Characteristic to be specified       26         14.3.2 Method of measurement       26         14.4 Difference frequency distortion of second order       27         14.4.1 Characteristic to be specified       27         14.4.2 Method of measurement       27         15 Limiting characteristics       28         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16.1 Balance       28         16.2 Balance under working conditions       29         17 Equivalent sound pressure level due to inherent noise       29         17.1 Characteristic to be specified       29         17.2 Method of measurement       29         18 Ambient conditions       30			O	755106ef8246/sist-en-iec-60268-4-2019	25
14.2.1Characteristic to be specified2514.2.2Method of measurement2614.3Harmonic distortion of the $n^{th}$ order $(n=2,3,)$ 2614.3.1Characteristic to be specified2614.3.2Method of measurement2614.4Difference frequency distortion of second order2714.4.1Characteristic to be specified2714.4.2Method of measurement2715Limiting characteristics2815.1Rated maximum permissible peak sound pressure2815.2Overload sound pressure2815.2.1Characteristic to be specified2815.2.2Method of measurement2816Balance2816.1Balance of the microphone output2816.2Balance under working conditions2917Characteristic to be specified2917.1Characteristic to be specified2917.2Method of measurement2918Ambient conditions30					
14.2.2Method of measurement2614.3Harmonic distortion of the $n^{th}$ order ( $n=2,3,$ )2614.3.1Characteristic to be specified2614.3.2Method of measurement2614.4Difference frequency distortion of second order2714.4.1Characteristic to be specified2714.4.2Method of measurement2715Limiting characteristics2815.1Rated maximum permissible peak sound pressure2815.2Overload sound pressure2815.2.1Characteristic to be specified2815.2.2Method of measurement2816Balance2816.1Balance of the microphone output2816.2Balance under working conditions2917Characteristic to be specified2917.1Characteristic to be specified2917.2Method of measurement2918Ambient conditions30		–			
14.3Harmonic distortion of the $n^{th}$ order $(n=2,3,)$ 2614.3.1Characteristic to be specified2614.3.2Method of measurement2614.4Difference frequency distortion of second order2714.4.1Characteristic to be specified2714.4.2Method of measurement2715Limiting characteristics2815.1Rated maximum permissible peak sound pressure2815.2Overload sound pressure2815.2.1Characteristic to be specified2815.2.2Method of measurement2816Balance2816.1Balance of the microphone output2816.2Balance under working conditions2917Equivalent sound pressure level due to inherent noise2917.1Characteristic to be specified2917.2Method of measurement2918Ambient conditions30				·	
14.3.1       Characteristic to be specified       26         14.3.2       Method of measurement       26         14.4       Difference frequency distortion of second order       27         14.4.1       Characteristic to be specified       27         14.4.2       Method of measurement       27         15       Limiting characteristics       28         15.1       Rated maximum permissible peak sound pressure       28         15.2       Overload sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16.1       Balance       28         16.2       Balance under working conditions       29         17       Equivalent sound pressure level due to inherent noise       29         17.1       Characteristic to be specified       29         17.2       Method of measurement       29         18       Ambient conditions       30					
14.3.2       Method of measurement       26         14.4       Difference frequency distortion of second order       27         14.4.1       Characteristic to be specified       27         14.4.2       Method of measurement       27         15       Limiting characteristics       28         15.1       Rated maximum permissible peak sound pressure       28         15.2       Overload sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16       Balance       28         16.1       Balance of the microphone output       28         16.2       Balance under working conditions       29         17       Equivalent sound pressure level due to inherent noise       29         17.1       Characteristic to be specified       29         17.2       Method of measurement       29         18       Ambient conditions       30				,	
14.4 Difference frequency distortion of second order       27         14.4.1 Characteristic to be specified       27         14.4.2 Method of measurement       27         15 Limiting characteristics       28         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16 Balance       28         16.1 Balance of the microphone output       28         16.2 Balance under working conditions       29         17 Equivalent sound pressure level due to inherent noise       29         17.1 Characteristic to be specified       29         17.2 Method of measurement       29         18 Ambient conditions       30				·	
14.4.1       Characteristic to be specified       27         14.4.2       Method of measurement       27         15       Limiting characteristics       28         15.1       Rated maximum permissible peak sound pressure       28         15.2       Overload sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16       Balance       28         16.1       Balance of the microphone output       28         16.2       Balance under working conditions       29         17       Equivalent sound pressure level due to inherent noise       29         17.1       Characteristic to be specified       29         17.2       Method of measurement       29         18       Ambient conditions       30		_			
14.4.2       Method of measurement       27         15       Limiting characteristics       28         15.1       Rated maximum permissible peak sound pressure       28         15.2       Overload sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16       Balance       28         16.1       Balance of the microphone output       28         16.2       Balance under working conditions       29         17       Equivalent sound pressure level due to inherent noise       29         17.1       Characteristic to be specified       29         17.2       Method of measurement       29         18       Ambient conditions       30				•	
15 Limiting characteristics       28         15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16 Balance       28         16.1 Balance of the microphone output       28         16.2 Balance under working conditions       29         17 Equivalent sound pressure level due to inherent noise       29         17.1 Characteristic to be specified       29         17.2 Method of measurement       29         18 Ambient conditions       30				·	
15.1 Rated maximum permissible peak sound pressure       28         15.2 Overload sound pressure       28         15.2.1 Characteristic to be specified       28         15.2.2 Method of measurement       28         16 Balance       28         16.1 Balance of the microphone output       28         16.2 Balance under working conditions       29         17 Equivalent sound pressure level due to inherent noise       29         17.1 Characteristic to be specified       29         17.2 Method of measurement       29         18 Ambient conditions       30	4-				
15.2       Overload sound pressure       28         15.2.1       Characteristic to be specified       28         15.2.2       Method of measurement       28         16       Balance       28         16.1       Balance of the microphone output       28         16.2       Balance under working conditions       29         17       Equivalent sound pressure level due to inherent noise       29         17.1       Characteristic to be specified       29         17.2       Method of measurement       29         18       Ambient conditions       30			•		
15.2.1Characteristic to be specified2815.2.2Method of measurement2816Balance2816.1Balance of the microphone output2816.2Balance under working conditions2917Equivalent sound pressure level due to inherent noise2917.1Characteristic to be specified2917.2Method of measurement2918Ambient conditions30					
15.2.2 Method of measurement2816 Balance2816.1 Balance of the microphone output2816.2 Balance under working conditions2917 Equivalent sound pressure level due to inherent noise2917.1 Characteristic to be specified2917.2 Method of measurement2918 Ambient conditions30				•	
16 Balance2816.1 Balance of the microphone output2816.2 Balance under working conditions2917 Equivalent sound pressure level due to inherent noise2917.1 Characteristic to be specified2917.2 Method of measurement2918 Ambient conditions30		_		·	
16.1 Balance of the microphone output2816.2 Balance under working conditions2917 Equivalent sound pressure level due to inherent noise2917.1 Characteristic to be specified2917.2 Method of measurement2918 Ambient conditions30			_		
16.2 Balance under working conditions2917 Equivalent sound pressure level due to inherent noise2917.1 Characteristic to be specified2917.2 Method of measurement2918 Ambient conditions30	16	Balar	nce		28
17 Equivalent sound pressure level due to inherent noise2917.1 Characteristic to be specified2917.2 Method of measurement2918 Ambient conditions30		16.1	Bala	nce of the microphone output	28
17.1 Characteristic to be specified2917.2 Method of measurement2918 Ambient conditions30		16.2	Bala	nce under working conditions	29
17.2 Method of measurement2918 Ambient conditions30	17	Equiv	valen	t sound pressure level due to inherent noise	29
17.2 Method of measurement2918 Ambient conditions30		17.1	Cha	racteristic to be specified	29
		17.2	Meth	nod of measurement	29
19.1 Conoral	18	Ambi	ent c	onditions	30
10.1 General0		18.1	Gen	eral	30

	18.2	Pressure range	30
	18.3	Temperature range	30
	18.4	Relative humidity range	30
19	Exter	nal influences	30
	19.1	General	30
	19.1.	1 Specification and methods of measurement	30
	19.1.	2 Other external interferences	31
	19.2	Equivalent sound pressure due to mechanical vibration	31
	19.2.	1 Characteristic to be specified	31
	19.2.	2 Method of measurement	31
	19.3	Equivalent sound pressure due to wind	31
	19.3.	1 Characteristic to be specified	31
	19.3.	2 Method of measurement	32
	19.4	Transient equivalent sound pressure due to "pop" effect	35
	19.4.	1 General	35
	19.4.	2 Characteristic to be specified	35
	19.4.	3 Method of measurement	36
20	Elect	romagnetic compatibility (EMC)	37
	20.1	Regulatory requirements	37
	20.2	Requirements for preserving programme quality	37
	20.3	Requirements for preserving programme quality  Performance criteria  ANDARD PREVIEW	38
	20.3.	1 Criterion A(etandarde itch ai)	38
	20.3.	1 Criterion A (standards.iteh.ai) 2 Criterion B	38
	20.4	Testing for immunity to disturbances in the presence of acoustical noise	39
	20.5	Immunity to frequency-modulated radiated disturbances 4605-8342-	39
	20.6	Immunity to magnetic fields f8246/sist-en-iec-60268-4-2019	39
	20.7	Immunity to ripple on d.c. power supply	
	20.8	Permanent magnetic field	40
	20.9	Evaluation and reporting of the test results	40
21	Physi	ical characteristics	40
	21.1	Dimensions	40
	21.2	Weight	40
	21.3	Cables and connectors	40
22	Class	sification of the characteristics to be specified	40
An	nex A (	normative) Additional characteristics	43
	•	Characteristic sensitivity for speech	
	A.1.1		
	A.1.2	·	
		Front-to-rear sensitivity index (0° – 180°)	
	A.2.1	• • • •	
	A.2.2	·	
		Noise-cancelling index	
	A.3.1	· ·	
	A.3.2		
	_	Special characteristics for stereo microphones	
	A.4.1	·	
	A.4.2		
	A.4.3		
		, •	. •

Annex B (informative) Sound insulation device	46
Annex C (informative) Recommendations for professional digital microphones	47
C.1 General	47
C.2 Data sheets for digital microphones	47
Annex D (informative) Recommended method for measuring noise levels according to ITU-R BS.468-4 in the digital domain	50
D.1 General	50
D.2 Recommended method	
D.3 Matlab code	51
Bibliography	54
Figure 1 – Balance of the output	28
Figure 2 – Balance under working conditions	
Figure 3 – Measurement set-up for wind influence	
Figure 4 – Wind generators, type 1 (Figure 4a) and type 2 (Figure 4b)	
Figure 5 – Electrical and mechanical setup for the measuring of the "pop" effect	
Figure B.1 – Sound insulation device	
Figure D.1 – ITU weighting filter for weighted and unweighted measurements	
Figure D.2 – Peak value rectifier scheme DARD PREVIEW	51
Table 1 – Reverberation time of the empty room s.iteh.ai)	15
Table 2 – Examples of EMC regulations and standards	37
Table 3 – Examples of EMC regulations and standards.  SIST EN IEC 60268-4-2019  Table 3 – Basic EMC standards and their application to microphones.  Table 3 – Basic EMC standards and their application to microphones.	38
Table 4 – Classification of characteristics 6/sist-en-icc-60268-4-2019	41
Table A.1 – Speech power weighting factor at octave-band centre frequencies	
Table C.1 – Classification of the characteristics recommended to be specified	
Table C.2 – Additional digital characteristics to be specified	
Table D.1 – Time constants for the two PVRs	51

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## **SOUND SYSTEM EQUIPMENT -**

## Part 4: Microphones

## **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity. EC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.

  SIST EN IEC 60268-4:2019
- 5) IEC itself does not provide any attestation of conformity independent certification bodies provide conformity assessment services and, in some areas access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60268-4 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

This sixth edition cancels and replaces the fifth edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Subclause 19.4 on "pop" measurement replaces Annex C;
- b) new Annex D for noise measurements in the digital domain.

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/2992/CDV	100/3109/RVC

IEC 60268-4:2018 © IEC 2018

**-7-**

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60268 series, under the general title *Sound system equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN IEC 60268-4:2019 https://standards.iteh.ai/catalog/standards/sist/907e5463-731a-4605-8342-755106ef8246/sist-en-iec-60268-4-2019

## SOUND SYSTEM EQUIPMENT -

## Part 4: Microphones

## 1 Scope

This part of IEC 60268 specifies methods of measurement for the electrical impedance, sensitivity, directional response pattern, dynamic range and external influences of sound system microphones, and also details the characteristics to be specified by the manufacturer.

It applies to sound system microphones for all applications for speech and music. It does not apply to measurement microphones, but it does apply to each audio channel of microphones having more than one channel, for example for stereo or similar use. It is also applicable to flush-mounted microphones and to the analogue characteristics of microphones with digital audio output.

For the purposes of this International Standard, a microphone includes all such devices as transformers, pre-amplifiers, or other elements that form an integral part of the microphone, up to the output terminals specified by the manufacturer.

The major characteristics of a microphone are considered in Clauses 6 to 21. Additional characteristics are considered in Annex A and Annex C. Standards.iteh.ai

NOTE The characteristics specified in this document do not describe the subjective response of the microphone. Further work is necessary to find new definitions and measurement procedures for a later introduction of objective characteristics for at least some of the subjective descriptions used to describe microphone performance.

755106ef8246/sist-en-iec-60268-4-2019

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 35:2016, Electromagnetic compatibility of multimedia equipment – Immunity requirements

IEC 60268-1:1985, Sound system equipment - Part 1: General

IEC 60268-1:1985/AMD1:1988 IEC 60268-1:1985/AMD2:1988

IEC 60268-2:1987, Sound system equipment – Part 2: Explanation of general terms and calculation methods

IEC 60268-2:1987/AMD1:1991

IEC 60268-3:2013, Sound system equipment – Part 3: Amplifiers

IEC 60268-5:2003, Sound system equipment – Part 5: Loudspeakers

IEC 60268-5:2003/AMD1:2007

IEC 60268-11:1987, Sound system equipment – Part 11: Application of connectors for the interconnection of sound system components

IEC 60268-11:1987/AMD1:1989 IEC 60268-11:1987/AMD2:1991 IEC 60268-4:2018 © IEC 2018

\_ 9 \_

IEC 60268-12:1987, Sound system equipment – Part 12: Application of connectors for broadcast and similar use

IEC 60268-12:1987/AMD1:1991 IEC 60268-12:1987/AMD2:1994

IEC 61000-4-2:2008, Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test

IEC 61000-4-3:2006, Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test IEC 61000-4-3:2006/AMD1:2007 IEC 61000-4-3:2006/AMD2:2010

IEC 61000-4-4:2012, Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test

IEC 61000-4-6:2013, Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

IEC 61000-4-8:2009, Electromagnetic compatibility (EMC) – Part 4-8: Testing and measurement techniques – Power frequency magnetic field immunity test

IEC 61000-4-16:2015, Electromagnetic compatibility (EMC) — Part 4-16: Testing and measurement techniques — Test for immunity to conducted, common mode disturbances in the frequency range 0 Hz to 150 kHz ndards.iteh.ai)

IEC 61000-4-17:1999, Electromagnetic compatibility (EMC) – Part 4-17: Testing and measurement techniques – Ripple on d.c. input power port immunity test 61000-4-17:1999/AMD1:2001 755106ef8246/sist-en-iec-60268-4-2019

IEC 61260-1:2014, Electroacoustics – Octave-band and fractional-octave-band filters – Part 1: Specifications

IEC 61938:2013, Multimedia systems – Guide to the recommended characteristics of analogue interfaces to achieve interoperability

ITU-T Recommendation P.51:1996, Artificial mouth

EN 55103-2:2009, Electromagnetic compatibility – Product family standard for audio, video, audio-visual and entertainment lighting control apparatus for professional use – Part 2: Immunity

EN 300 422-2 V1.3.1:2011, Electromagnetic compatibility and radio spectrum matters (ERM) – Wireless microphones in the 25 MHz to 3 GHz frequency range – Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60268-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

IEC Electropedia: available at http://www.electropedia.org/