

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11

Fax: +41 22 749 09 47

Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

- Formatted: Font: Bold
- Formatted: Font: Bold
- Formatted: HeaderCentered, Line spacing: single
- Formatted: Left: 1.5 cm, Right: 1.5 cm, Header distance from edge: 1.27 cm, Footer distance from
- Commented [eXtyle1]: The reference "ISO 2024" is to a withdrawn standard
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: French (France)
- Formatted: French (France)
- Formatted: French (France)
- Formatted: zzCopyright address, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO/FDIS 17491-4

<https://standards.itih.ai/catalog/standards/iso/d1afd9fd-812c-46ac-a8d9-ccdc024e1134/iso-fdis-17491-4>

Formatted: FooterPageRomanNumber

Formatted: Font: Bold
Formatted: HeaderCentered, Left, Line spacing: single

Contents

Foreword.....v

Introduction.....vii

1 Scope.....1

2 Normative references.....1

3 Terms and definitions.....1

4 Principle of test method.....2

5 Test liquid.....2

6 Apparatus and test subjects.....3

7 Preparation of the test subjects for the spray test.....5

8 Preparation of the spray application system.....6

8.1 Test liquid.....6

8.2 Nozzle output.....6

8.3 Distribution of the spray liquid and alignment of spray nozzles.....6

9 Procedure.....7

9.1 Spray procedure.....7

9.2 Procedure for penetration and stains.....8

10 Test report.....8

Annex A (informative) The non-absorbent fabric and absorbent overall.....10

Annex B (informative) Body measurements and selection sizing of the test garment.....11

Annex C (normative) Donning and doffing of test garment and marking of stain.....13

Annex D (informative) Interlaboratory study (ILS) observations for ISO 17491-4 Methods A and B.....15

Bibliography.....19

Foreword — iv

Introduction — vi

1 — Scope — 1

2 — Normative references — 1

3 — Terms and definitions — 1

4 — Principle of test method — 2

5 — Test liquid — 2

6 — Apparatus and test subjects — 2

6.1 — Absorbent overall — 2

6.2 — Calibrated stain — 3

6.3 — Turntable — 3

6.4 — Test liquid container — 3

6.5 — Hydraulic pump — 3

6.6 — Stopwatch — 3

Formatted: Font: 10 pt
Formatted: Font: 10 pt
Formatted: Font: 10 pt
Formatted: FooterCentered, Left, Line spacing: single
Formatted: Font: 11 pt
Formatted: FooterPageRomanNumber, Left, Space After: 0 pt, Line spacing: single

Formatted: Font: Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Line spacing: single

6.7 Spray booth 3

6.8 Spray boom 3

6.9 Hydraulic nozzles 4

6.10 Test Subjects and test subject dimensions 5

7 Preparation of the test subjects for the spray test 5

8 Preparation of the spray application system 5

8.1 Test liquid 5

8.2 Nozzle output 5

8.3 Distribution of the spray liquid and alignment of spray nozzles 6

9 Procedure 7

9.1 Spray procedure 7

9.2 Procedure for penetration and stains 7

10 Test report 8

Annex A (informative) The non-absorbent fabric and absorbent overall 9

Annex B (informative) Body Measurements and Selection Sizing of the Test Garment 10

Annex C (Normative) Donning and doffing of test garment and marking of stain 12

Annex D (informative) Inter-laboratory Study (ILS) observations for ISO 17491-4 Method A and B 14

Bibliography 17

Standards
(https://standards.iteh.ai)
Document Preview

ISO/FDIS 17491-4

https://standards.iteh.ai/catalog/standards/iso/d1afd9fd-812c-46ac-a8d9-ccdc024e1134/iso-fdis-17491-4

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 94, *Personal safety — Personal protective equipment*, Subcommittee SC 13, *Protective clothing*, in collaboration with the European Committee for Standardization, (CEN) Technical Committee CEN/TC 162, *Protective clothing including hand and arm protection and lifejackets*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 17491-4:2008), which has been technically revised. It also incorporates the Amendment ISO 17491-4:2008/Amd.1:2016.

The main changes are as follows:

- specifications for test liquid have been revised/added;
- **Clause 6** has been revised to provide more specificity. Specification have been changed and/or revised for absorbent overall, calibrated stain, turntable, spray booth, spray boom, hydraulic nozzles in **Clause 6** and other applicable clauses;
- details for the selection of the right overall size have been added in **6.10.6.10** as well as in **Annex B**;
- **9.3.3** has been revised and heading changed to "Distribution of the spray liquid and alignment of spray nozzles.";
- figure and additional information have been added in **9.1.1** to provide more specificity;

Formatted: Font: Bold

Formatted: HeaderCentered, Left, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: FooterCentered, Left, Line spacing: single

Formatted: Font: 11 pt

Formatted: FooterPageRomanNumber, Left, Space After: 0 pt, Line spacing: single

ISO/FDIS 17491-4:2023(E)2024(en)

- inclusion of **Annex A** on absorbent fabric for the detector suit and non-absorbent fabric for the calibration pattern;
- inclusion of **Annex B** on test subject size measurement and right overall size fitting;
- inclusion of **Annex C** on right donning and doffing, as well as stain area measurement;
- inclusion of **Annex D** with the ILT results.

A list of all parts in the ISO 17491 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Formatted: Font: Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Line spacing: single

Commented [eXtyles2]: Invalid reference: "ISO 17491 series"

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 17491-4
<https://standards.iteh.ai/catalog/standards/iso/d1afd9fd-812c-46ac-a8d9-ccdc024e1134/iso-fdis-17491-4>

Formatted: FooterPageRomanNumber

Formatted: Font: Bold

Formatted: HeaderCentered, Left, Line spacing: single

Introduction

This document describes a test method for determining the spray penetration resistance of chemical protective clothing Type 4 (with spray-tight connections between different parts of the clothing and, if applicable, between the clothing and other items of personal protective equipment) and Type 6 (limited performance protective clothing).

Such clothing comprises one or more items covering the full surface of the body and is intended to be worn under conditions where there is a risk of exposure to a spray of a liquid chemical. Other requirements with regard to this type of clothing and its constituent materials can be found in the respective product standards^[1].

Interlaboratory testing has shown that this test method is a repeatable pass/fail method.

A document on the selection, use and maintenance of chemical protective clothing is available^[2].

iTeh Standards
(https://standards.itih.ai)
Document Preview

ISO/FDIS 17491-4

https://standards.itih.ai/catalog/standards/iso/d1afd9fd-812c-46ac-a8d9-ccdc024e1134/iso-fdis-17491-4

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: FooterCentered, Left, Line spacing: single

Formatted: Font: 11 pt

Formatted: FooterPageRomanNumber, Left, Space After: 0 pt, Line spacing: single

Protective clothing — Test methods for clothing providing protection against chemicals

Part 4: Determination of resistance to penetration by a spray of liquid (Sprayspray test)

CAUTION — Some of the procedures specified in this document involve the use of processes which could lead to hazardous situations and hence appropriate precautions should be taken.

1 Scope

This document specifies the test method for determining the resistance of chemical protective clothing to penetration by sprays of liquid chemicals at two different levels of intensity:

- a) Method A: low-level spray test. This is applicable to clothing that covers the full body surface and is intended to be worn when there is a potential risk of exposure to small quantities of spray or accidental low-volume splashes of a liquid chemical.
- b) Method B: high-level spray test. This is applicable to clothing with spray-tight connections between different parts of the clothing and, if applicable, between the clothing and other items of personal protective equipment, which covers the full body surface and which is intended to be worn when there is a risk of exposure to sprayed liquid chemical.

This document does not apply to chemical permeation resistance of the materials from which the chemical protective clothing is made.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

<std>ISO 11610, Protective clothing — Vocabulary</std>

ISO 11610, Protective clothing — Vocabulary

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11610 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

Formatted: Left: 1.5 cm, Right: 1.5 cm, Section start: New page, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Formatted: Main Title 2, Space After: 0 pt, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Numbered + Level: 1 + Numbering Style: a, b, c, ... + Start at: 1 + Alignment: Left + Aligned at: 0 cm + Indent at: 0 cm, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Commented [eXtyle3]: The URL <https://www.iso.org/obp> has been redirected to <https://www.iso.org/obp/ui>. Please verify the URL.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: 11 pt

Formatted: Left, Space After: 0 pt, Line spacing: single

Formatted: Font: Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

3.1

absorbent overall

overall made from an absorbent material, worn under the test suit and intended for collecting liquid penetration during spray and jet testing of chemical protective clothing

3.2

calibrated stain

visible stain, with a defined minimum area, generated by dropping a specified quantity of test liquid on to an absorbent overall (3.1)(3.1)

Note 1 to entry: The calibrated stain is used to measure liquid penetration during spray and jet testing of chemical protective clothing.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

4 Principle of test method

An aqueous spray, containing a visible dye tracer, is directed under controlled conditions at the chemical protective clothing worn by a human test subject. Inspection of the inside surface of the clothing and the outside surface of the absorbent overall worn under the test garment allows any points of inward leakage to be identified.

An interlab was performed and the results and conclusion can be found in Annex D-Annex D.

5 Test liquid

To prepare the test chemical add methyl blue dye and dye stabilizer prior to adding the surfactant to water. The temperature of the test liquid shall be between 20 °C and 30 °C.

For methods A and B, the concentration of the methyl blue dye (CAS number 28983-56-4) shall be (0,2 ± 0,02) g/l. The dye stabilizer shall be analytical grade citric acid (CAS number 77-92-9) with a concentration of (2,45 ± 0,05) g/l.

The surfactant is then added to achieve the required surface tension. Mixtures such as dish washing detergent that include other ingredients are not considered surfactants and shall not be used.

a) a) For method A: a surface tension of $(52,0 \pm 7,5) \times 10^{-3}$ N/m;

b) b) For method B: a surface tension of $(30,0 \pm 5,0) \times 10^{-3}$ N/m.

NOTE 1 Surfactants: Genapol LRO liquid (1 sodium lauryl ether sulfate (CAS number [009004-82-4])) that can be used to achieve the required surface tension at the concentration of 0,03 ml/l for method A and 0,5 ml/l for method B. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the products named. Equivalent products can be used if they can be shown to lead to the same results.

Formatted: Numbered + Level: 1 + Numbering Style: a, b, c, ... + Start at: 1 + Alignment: Left + Aligned at: 0 cm + Indent at: 0 cm, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

NOTE 2 To measure the surface tension within the stated tolerance, any suitable method can be used, e.g., a wright torsion balance using a standard 12 mm diameter platinum ring.

It shall be ensured that the surface tension and temperature of the test liquid are stable throughout the test, i.e., the surface tension of the liquid leaving the nozzle as well as the tension of the liquid in the tank shall meet the requirements. This shall be verified before and after each day of test and shall meet all the above requirement in this clause according to either Method A or Method B.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

¹ Genapol LRO liquid is an example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of this product.

Formatted: FooterPageRomanNumber