



International
Standard

ISO/IEC 23090-3

**Information technology — Coded
representation of immersive media —**

Part 3:

Versatile video coding

*Technologies de l'information — Représentation codée de média
immersifs —*

Partie 3: Codage vidéo polyvalent

**Third edition
2024-07**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/IEC 23090-3:2024

<https://standards.iteh.ai/catalog/standards/iso/7495d761-3c62-4936-8c6b-2e7ae2a033ba/iso-iec-23090-3-2024>

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/IEC 23090-3:2024

<https://standards.iteh.ai/catalog/standards/iso/7495d761-3c62-4936-8c6b-2e7ae2a033ba/iso-iec-23090-3-2024>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Foreword.....	vi
Introduction	vii
1 Scope.....	1
2 Normative references	1
3 Terms and definitions.....	1
4 Abbreviated terms	17
5 Conventions	19
5.1 General.....	19
5.2 Arithmetic operators	19
5.3 Logical operators.....	20
5.4 Relational operators	20
5.5 Bit-wise operators	20
5.6 Assignment operators	21
5.7 Range notation	21
5.8 Mathematical functions	21
5.9 Order of operation precedence	22
5.10 Variables, syntax elements and tables.....	22
5.11 Text description of logical operations.....	24
5.12 Processes	25
6 Bitstream and picture formats, partitionings, scanning processes and neighbouring relationships	25
6.1 Bitstream formats	25
6.2 Source, decoded and output picture formats	26
6.3 Partitioning of pictures, subpictures, slices, tiles, and CTUs.....	28
6.3.1 Partitioning of pictures into subpictures, slices, and tiles.....	28
6.3.2 Block, quadtree and multi-type tree structures.....	30
6.3.3 Spatial or component-wise partitionings	31
6.4 Availability processes.....	32
6.4.1 Allowed quad split process	32
6.4.2 Allowed binary split process	33
6.4.3 Allowed ternary split process	35
6.4.4 Derivation process for neighbouring block availability	36
6.5 Scanning processes.....	36
6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes	36
6.5.2 Up-right diagonal scan order array initialization process	41
6.5.3 Horizontal and vertical traverse scan order array initialization process.....	41
7 Syntax and semantics.....	42
7.1 Method of specifying syntax in tabular form	42
7.2 Specification of syntax functions and descriptors.....	43
7.3 Syntax in tabular form	45
7.3.1 NAL unit syntax	45
7.3.2 Raw byte sequence payloads, trailing bits and byte alignment syntax	46
7.3.3 Profile, tier, and level syntax	65
7.3.4 DPB parameters syntax.....	68
7.3.5 Timing and HRD parameters syntax	68
7.3.6 Supplemental enhancement information message syntax	69
7.3.7 Slice header syntax.....	70

7.3.8	Weighted prediction parameters syntax	72
7.3.9	Reference picture lists syntax	73
7.3.10	Reference picture list structure syntax	74
7.3.11	Slice data syntax	74
7.4	Semantics	97
7.4.1	General	97
7.4.2	NAL unit semantics	97
7.4.3	Raw byte sequence payloads, trailing bits and byte alignment semantics	106
7.4.4	Profile, tier, and level semantics	166
7.4.5	DPB parameters semantics	173
7.4.6	Timing and HRD parameters semantics	174
7.4.7	Supplemental enhancement information message semantics	178
7.4.8	Slice header semantics	178
7.4.9	Weighted prediction parameters semantics	189
7.4.10	Reference picture lists semantics	191
7.4.11	Reference picture list structure semantics	192
7.4.12	Slice data semantics	193
8	Decoding process	220
8.1	General decoding process	220
8.2	NAL unit decoding process	223
8.3	Slice decoding process	224
8.3.1	Decoding process for picture order count	224
8.3.2	Decoding process for reference picture lists construction	225
8.3.3	Decoding process for reference picture marking	231
8.3.4	Decoding process for generating unavailable reference pictures	232
8.3.5	Decoding process for symmetric motion vector difference reference indices	233
8.3.6	Decoding process for collocated picture and no backward prediction	234
8.4	Decoding process for coding units coded in intra prediction mode	234
8.4.1	General decoding process for coding units coded in intra prediction mode	234
8.4.2	Derivation process for luma intra prediction mode	236
8.4.3	Derivation process for chroma intra prediction mode	239
8.4.4	Cross-component chroma intra prediction mode checking process	241
8.4.5	Decoding process for intra blocks	243
8.5	Decoding process for coding units coded in inter prediction mode	278
8.5.1	General decoding process for coding units coded in inter prediction mode	278
8.5.2	Derivation process for motion vector components and reference indices	284
8.5.3	Decoder-side motion vector refinement process	306
8.5.4	Derivation process for geometric partitioning mode motion vector components and reference indices	312
8.5.5	Derivation process for subblock motion vector components and reference indices	314
8.5.6	Decoding process for inter blocks	345
8.5.7	Decoding process for geometric partitioning mode inter blocks	370
8.5.8	Decoding process for the residual signal of coding blocks coded in inter prediction mode	376
8.5.9	Decoding process for the reconstructed signal of chroma coding blocks coded in inter prediction mode	378
8.6	Decoding process for coding units coded in IBC prediction mode	380
8.6.1	General decoding process for coding units coded in IBC prediction mode	380
8.6.2	Derivation process for block vector components for IBC blocks	383
8.6.3	Decoding process for IBC blocks	387
8.7	Scaling, transformation and array construction process	388
8.7.1	Derivation process for quantization parameters	388
8.7.2	Scaling and transformation process	390
8.7.3	Scaling process for transform coefficients	391
8.7.4	Transformation process for scaled transform coefficients	394

8.7.5	Picture reconstruction process	415
8.8	In-loop filter process	419
8.8.1	General	419
8.8.2	Picture inverse mapping process for luma samples	420
8.8.3	Deblocking filter process.....	420
8.8.4	Sample adaptive offset process	451
8.8.5	Adaptive loop filter process	454
9	Parsing process	467
9.1	General.....	467
9.2	Parsing process for k-th order Exp-Golomb codes	467
9.2.1	General	467
9.2.2	Mapping process for signed Exp-Golomb codes	469
9.3	CABAC parsing process for slice data	469
9.3.1	General	469
9.3.2	Initialization process.....	471
9.3.3	Binarization process.....	494
9.3.4	Decoding process flow.....	505
Annex A (normative)	Profiles, tiers and levels	523
Annex B (normative)	Byte stream format	543
Annex C (normative)	Hypothetical reference decoder	546
Annex D (normative)	Supplemental enhancement information and use of SEI and VUI	572

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/IEC 23090-3:2024](https://standards.iteh.ai/catalog/standards/iso/7495d761-3c62-4936-8c6b-2e7ae2a033ba/iso-iec-23090-3-2024)

<https://standards.iteh.ai/catalog/standards/iso/7495d761-3c62-4936-8c6b-2e7ae2a033ba/iso-iec-23090-3-2024>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T (as ITU-T H.266).

This third edition cancels and replaces the second edition (ISO/IEC 23090-3:2022), which has been technically revised.

The main changes are as follows:

- the specification of level 15.5 for the video profiles, to provide a suitable label for bitstreams that can exceed the limits of all other specified levels,
- the addition of support for the green metadata SEI message specified in ISO/IEC 23001-11, the video decoding interface SEI envelope SEI message specified in ISO/IEC 23090-13, and the neural-network post-filter characteristics, neural-network activation, and phase indication SEI messages specified in Rec. ITU-T H.274 | ISO/IEC 23002-7.

A list of all parts in the ISO/IEC 23090 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

Purpose

This document specifies a video coding technology known as versatile video coding. It has been designed with two primary goals. The first of these is to specify a video coding technology with a compression capability that is substantially beyond that of the prior generations of such standards, and the second is for this technology to be highly versatile for effective use in a broader range of applications than that addressed by prior standards. Some key application areas for the use of this document particularly include ultra-high-definition video (e.g., with 3840×2160 or 7620×4320 picture resolution and bit depth of 10 bits as specified in Rec. ITU-R BT.2100), video with a high dynamic range and wide colour gamut (e.g., with the perceptual quantization or hybrid log-gamma transfer characteristics specified in Rec. ITU-R BT.2100), and video for immersive media applications such as 360° omnidirectional video projected using a common projection format such as the equirectangular or cubemap projection formats, in addition to the applications that have commonly been addressed by prior video coding standards.

Profiles, tiers, and levels

This document is designed to be versatile in the sense that it serves a wide range of applications, bit rates, resolutions, qualities, and services. Applications include, but are not limited to, video coding for digital storage media, television broadcasting, video streaming services, real-time communication. In the course of creating this document, various requirements from typical applications have been considered, necessary algorithmic elements have been developed, and these have been integrated into a single syntax. Hence, this document is designed to facilitate video data interchange among different applications.

Considering the practicality of implementing the full syntax of this document, however, a limited number of subsets of the syntax are also stipulated by means of "profiles", "tiers", and "levels". These and other related terms are formally defined in Clause 3.

A "profile" is a subset of the entire bitstream syntax that is specified in this document. Within the bounds imposed by the syntax of a given profile it is still possible to require a very large variation in the performance of encoders and decoders depending upon the values taken by syntax elements in the bitstream, such as the specified size of the decoded pictures. In many applications, it is currently neither practical nor economical to implement a decoder capable of dealing with all hypothetical uses of the syntax within a particular profile.

In order to deal with this problem, "tiers" and "levels" are specified within each profile. A level of a tier is a specified set of constraints imposed on values of the syntax elements in the bitstream. Some of these constraints are expressed as simple limits on values, while others take the form of constraints on arithmetic combinations of values (e.g. picture width multiplied by picture height multiplied by number of pictures decoded per second). A level specified for a lower tier is more constrained than a level specified for a higher tier.

Coded video content conforming to this document uses a common syntax. In order to achieve a subset of the complete syntax, flags, parameters, and other syntax elements are included in the bitstream that signal the presence or absence of syntactic elements that occur later in the bitstream.

Encoding process, decoding process, and use of VUI parameters and SEI messages

Any encoding process that produces bitstream data that conforms to the specified bitstream syntax format requirements of this document is considered to be in conformance with the requirements of this document. The decoding process is specified such that all decoders that conform to a specified combination of capabilities known as the profile, tier, and level will produce numerically identical cropped decoded output pictures when invoking the decoding process associated with that profile for a bitstream conforming to that profile, tier and level. Any decoding process that produces identical

cropped decoded output pictures to those produced by the process described herein (with the correct output order or output timing, as specified) is considered to be in conformance with the requirements of this document.

Rec. ITU-T H.274 | ISO/IEC 23002-7 specifies the syntax and semantics of the video usability information (VUI) parameters and supplemental enhancement information (SEI) messages that do not affect the conformance specifications in Annex C. These VUI parameters and SEI messages may be used together with this document.

Versions of this document

Rec. ITU-T H.266 | ISO/IEC 23090-3 version 1 refers to the first approved version of this document. The first edition published by ISO/IEC as ISO/IEC 23090-3:2021 corresponded to the first version.

Rec. ITU-T H.266 | ISO/IEC 23090-3 version 2 refers to the integrated text additionally containing operation range extensions, a new level (level 6.3), additional supplement enhancement information, and corrections to various minor defects in the prior content of the document. The second edition published by ISO/IEC as ISO/IEC 23090-3:2022 corresponded to the second version.

Rec. ITU-T H.266 | ISO/IEC 23090-3 version 3 (the current version) refers to the integrated text containing the specification of a new level (level 15.5) for the video profiles to provide a suitable label for bitstreams that can exceed the limits of all other specified levels, additional supplement enhancement information, and corrections to various minor defects in the prior content of the document. This document corresponds to the third version. At the time of publication of this document, a corresponding third edition of Rec. ITU-T H.266 was in preparation for publication by ITU-T.

Overview of the design characteristics

The coded representation specified in the syntax is designed to enable a high compression capability for a desired image or video quality. The algorithm is typically not mathematically lossless, as the exact source sample values are typically not preserved through the encoding and decoding processes, although some modes are included that provide lossless coding capability. A number of techniques are specified to enable highly efficient compression. Encoding algorithms (not specified within the scope of this document) may select between inter, intra, intra block copy (IBC), and palette coding for block-shaped regions of each picture. Inter coding uses motion vectors for block-based inter-picture prediction to exploit temporal statistical dependencies between different pictures, intra coding uses various spatial prediction modes to exploit spatial statistical dependencies in the source signal within the same picture, and intra block copy coding uses block displacement vectors to reference previously decoded regions of the same picture to exploit statistical similarities among different areas of the same picture. Motion vectors, intra prediction modes, and IBC block vectors are specified for a variety of block sizes in the picture. The prediction residual can then be further compressed using a spatial transform to remove spatial correlation inside a block before it is quantized, producing a possibly irreversible process that typically discards less important visual information while forming a close approximation to the source samples. Finally, the motion vectors, intra prediction modes, and block vectors can also be further compressed using a variety of prediction mechanisms, and, after prediction, are combined with the quantized transform coefficient information and encoded using arithmetic coding.

How to read this document

It is suggested that the reader starts with Clause 1 and moves on to Clause 3. Clause 6 should be read for the geometrical relationship of the source, input, and output of the decoder. Clause 7 specifies the order to parse syntax elements from the bitstream. See subclauses 7.1 to 7.3 for syntactical order and subclause 7.4 for semantics; e.g. the scope, restrictions, and conditions that are imposed on the syntax elements. The actual parsing for most syntax elements is specified in Clause 9. Finally, Clause 8 specifies how the syntax elements are mapped into decoded samples. Annexes A through D also form an integral part of this document.

Annex A specifies profiles, each being tailored to certain application domains, and defines the so-called tiers and levels of the profiles. Annex B specifies syntax and semantics of a byte stream format for delivery of coded video as an ordered stream of bytes. Annex C specifies the hypothetical reference decoder, bitstream conformance, decoder conformance, and the use of the hypothetical reference decoder to check bitstream and decoder conformance. Annex D specifies syntax and semantics for supplemental enhancement information (SEI) message payloads that affect the conformance specifications in Annex C. Rec. ITU-T H.274 | ISO/IEC 23002-7 specifies the syntax and semantics of the video usability information (VUI) parameters as well as SEI messages that do not affect the conformance specifications in Annex C. These VUI parameters and SEI messages may be used together with this document.

The term "this document" is used to refer to this Recommendation | International Standard.

In this document, the following verbal forms are used:

- "shall" indicates a requirement;
- "should" indicates a recommendation;
- "may" indicates a permission;
- "can" indicates a possibility or a capability.

Information marked as "NOTE" is intended to assist the understanding or use of the document. "Notes to entry" used in Clause 3 provide additional information that supplements the terminological data and can contain provisions relating to the use of a term.

Itch Standards
(<https://standards.itch.ai>)
Document Preview

[ISO/IEC 23090-3:2024](https://standards.itch.ai/catalog/standards/iso/7495d761-3c62-4936-8c6b-2e7ae2a033ba/iso-iec-23090-3-2024)

<https://standards.itch.ai/catalog/standards/iso/7495d761-3c62-4936-8c6b-2e7ae2a033ba/iso-iec-23090-3-2024>

Information technology — Coded representation of immersive media —

Part 3: Versatile video coding

1 Scope

This document specifies a video coding technology known as versatile video coding (VVC), comprising a video coding technology with a compression capability that is substantially beyond that of the prior generations of such standards and with sufficient versatility for effective use in a broad range of applications.

Only the syntax format, semantics, and associated decoding process requirements are specified, while other matters such as pre-processing, the encoding process, system signalling and multiplexing, data loss recovery, post-processing, and video display are considered to be outside the scope of this document. Additionally, the internal processing steps performed within a decoder are also considered to be outside the scope of this document; only the externally observable output behaviour is required to conform to the specifications of this document.

This document is designed to be generic in the sense that it serves a wide range of applications, bit rates, resolutions, qualities and services. Applications include, but are not limited to, video coding for digital storage media, television broadcasting and real-time communication. In the course of creating This document, various requirements from typical applications have been considered, necessary algorithmic elements have been developed, and these have been integrated into a single syntax. Hence, this document is designed to facilitate video data interchange among different applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 23001-11, *Information Technology — MPEG Systems technologies — Part 11: Energy-efficient media consumption (green metadata)*

Rec. ITU-T H.274 | ISO/IEC 23002-7, *Versatile supplemental enhancement information messages for coded video bitstreams*

ISO/IEC 23090-13, *Information technology — Coded representation of immersive media — Part 13: Video decoding interface for immersive media*

Rec. ITU-T T.35, *Procedure for the allocation of ITU-T defined codes for non standard facilities*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1**access unit**

set of *PUs* that belong to different *layers* and contain *coded pictures* associated with the same time for output from the *DPB*

3.2**adaptive colour transform**

cross-component transform applied to the decoded *residual* of a *coding unit* in the 4:4:4 colour format prior to reconstruction and loop filtering

3.3**adaptive loop filter**

filtering process that is applied as part of the *decoding process* and is controlled by parameters conveyed in an *APS*

3.4**ALF APS**

APS that controls the *ALF* process

3.5**adaptation parameter set**

syntax structure containing *syntax elements* that apply to zero or more *slices* as determined by zero or more *syntax elements* found in *slice headers*

3.6**associated GDR picture**

previous *GDR picture* (when present) in *decoding order*, for a particular picture with *nuh_layer_id* equal to a particular value *layerId*, that has *nuh_layer_id* equal to *layerId* and between which and the particular picture in *decoding order* there is no *IRAP picture* with *nuh_layer_id* equal to *layerId*

3.7**associated IRAP picture**

previous *IRAP picture* (when present) in *decoding order*, for a particular picture with *nuh_layer_id* equal to a particular value *layerId*, that has *nuh_layer_id* equal to *layerId* and between which and the particular picture in *decoding order* there is no *GDR picture* with *nuh_layer_id* equal to *layerId*

3.8**associated IRAP subpicture**

previous *IRAP subpicture* (when present) in *decoding order*, for a particular subpicture with *nuh_layer_id* equal to a particular value *layerId* and subpicture index equal to a particular value *subpicIdx*, that has *nuh_layer_id* equal to *layerId* and subpicture index equal to *subpicIdx* and between which and the particular subpicture in *decoding order* there is no *GDR subpicture* with *nuh_layer_id* equal to *layerId* and subpicture index equal to *subpicIdx*

3.9**associated non-VCL NAL unit**

non-VCL NAL unit (when present) for a *VCL NAL unit* where the *VCL NAL unit* is the *associated VCL NAL unit* of the *non-VCL NAL unit*

3.10**associated VCL NAL unit**

preceding *VCL NAL unit* in *decoding order* for a *non-VCL NAL unit* with *nal_unit_type* equal to *EOS_NUT*, *EOB_NUT*, *SUFFIX_APS_NUT*, *SUFFIX_SEI_NUT*, *FD_NUT*, *RSV_NVCL_27*, *UNSPEC_30*, or *UNSPEC_31*; or otherwise the next *VCL NAL unit* in *decoding order*

3.11**bin**

bit of a *bin string*

3.12**binarization**

set of *bin strings* for all possible values of a *syntax element*

3.13**binarization process**

unique mapping process of all possible values of a *syntax element* onto a set of *bin strings*

3.14**binary split**

split of a rectangular $M \times N$ *block* of samples into two *blocks* where a vertical split results in a first $(M / 2) \times N$ *block* and a second $(M / 2) \times N$ *block*, and a horizontal split results in a first $M \times (N / 2)$ *block* and a second $M \times (N / 2)$ *block*

3.15**bin string**

intermediate binary representation of values of *syntax elements* from the *binarization* of the *syntax element*

3.16**bi-predictive slice****B slice**

slice that is decoded using *intra prediction* or using *inter prediction* with at most two *motion vectors* and *reference indices* to *predict* the sample values of each *block*

3.17**bitstream**

sequence of bits, in the form of a *NAL unit stream* or a *byte stream*, that forms the representation of a sequence of *AUs* forming one or more coded video sequences (*CVSs*)

3.18**block**

$M \times N$ (M -column by N -row) array of samples, or an $M \times N$ array of *transform coefficients*

3.19**block vector**

two-dimensional vector that provides an offset from the coordinates of the current *coding block* to the coordinates of the reference block in the same decoded *slice*

3.20**byte**

sequence of 8 bits, within which, when written or read as a sequence of bit values, the left-most and right-most bits represent the most and least significant bits, respectively

3.21**byte-aligned**

<*bitstream*> positioned an integer multiple of 8 bits from the position of the first bit in the *bitstream*

3.22**byte-aligned**

<bit or *byte* or *syntax element*> position at which it appears in a *bitstream* is byte-aligned

3.23**byte stream**

encapsulation of a *NAL unit stream* into a series of *bytes* containing *start code prefixes* and *NAL units*

3.24**chroma**

sample array or single sample representing one of the two colour difference signals related to the primary colours, represented by the symbols Cb and Cr

Note 1 to entry: The term chroma is used rather than the term chrominance in order to avoid the implication of the use of linear light transfer characteristics that is often associated with the term chrominance.

3.25

CRA PU

PU in which the *coded picture* is a *CRA picture*

3.26

CRA picture

IRAP picture for which each *VCL NAL unit* has *nal_unit_type* equal to *CRA_NUT*

Note 1 to entry: A CRA picture does not use inter prediction in its decoding process, and could be the first picture in the bitstream in decoding order, or could appear later in the bitstream. A CRA picture could have associated RADL or RASL pictures. When a CRA picture has *NoOutputBeforeRecoveryFlag* equal to 1, the associated RASL pictures are not output by the decoder, because they might not be decodable, as they could contain references to pictures that are not present in the bitstream.

3.27

CRA subpicture

IRAP subpicture for which each *VCL NAL unit* has *nal_unit_type* equal to *CRA_NUT*

3.28

coded layer video sequence:

sequence of *PU*s with the same value of *nuh_layer_id* that consists, in *decoding order*, of a *CLVSS PU*, followed by zero or more *PU*s that are not *CLVSS PU*s, including all subsequent *PU*s up to but not including any subsequent *PU* that is a *CLVSS PU*

Note 1 to entry: A *CLVSS PU* could be an *IDR PU*, a *CRA PU*, or a *GDR PU*. The value of *NoOutputBeforeRecoveryFlag* is equal to 1 for each *IDR PU*, and each *CRA PU* that has *HandleCraAsClvsStartFlag* equal to 1, and each *CRA* or *GDR PU* that is the first *PU* in the layer of the bitstream in decoding order or the first *PU* in the layer of the bitstream that follows an *EOS NAL unit* in the layer in decoding order.

3.29

CLVSS PU

PU in which the *coded picture* is a *CLVSS picture*

3.30

CLVSS picture

coded picture that is an *IRAP picture* with *NoOutputBeforeRecoveryFlag* equal to 1 or a *GDR picture* with *NoOutputBeforeRecoveryFlag* equal to 1

3.31

coded picture

coded representation of a *picture* comprising *VCL NAL units* with a particular value of *nuh_layer_id* within an *AU* and containing all *CTUs* of the *picture*

3.32

coded picture buffer

first-in first-out buffer containing *DUs* in *decoding order* specified in the *hypothetical reference decoder*

Note 1 to entry: The hypothetical reference decoder is specified in Annex C.

3.33

coded representation

data element as represented in its coded form

3.34

coded slice NAL unit

NAL unit that contains a coded *slice*